



Kompakt Merkezi Sistem

Compact Central System



CMO-SM-04BE-0125S-T56G-F1-DT12

	C	M	O	S	M	-	04	B	E	-	0125	S	-	T	5	6	G	-	F1	-	DT12	-	BM
	FİRMA KODU / PRODUCING COMPANY																						
C	ÇÖZÜM END.SOĞ.SİS.A.Ş.																						
	ÜRÜN GRUBU / PRODUCT GROUP																						
M	MERKEZİ SİSTEM / CENTRAL SYSTEM																						
	KONDENSER ÜNİTESİ / CONDENSING UNIT																						
C	SU SOĞUTMA GRUBU / CHILLER																						
B	MONOBLOK / MONOBLOCK																						
	ÜRÜN KABİN MODELİ / PRODUCT CABIN MODEL																						
I	KABİNSİZ AÇIK TİP / WITHOUT CABIN																						
O	KABİNLİ / WITH CABIN																						
C	KOMPAKT KONDENSERLİ / COMPACT CABIN																						
	KOMPRESÖR TİPİ / COMPRESSOR TYPE																						
H	HERMETİK / HERMETIC	T	ÇİFT KADEME / TWO STAGE																				
S	SEMİ HERMETİK /SEMI HERMETIC	V	VİDALI/ SCREW																				
C	SCROLL / SCROLL	D	DİJİTAL SCROLL / DIGITAL SCROLL																				
	ÇALIŞMA SINIFI / WORKING CLASS																						
H	YÜKSEK SICAKLIK (+10 / +20) HT	B	ŞOKLAMA (-35 / -45) BLAST FREEZING																				
M	ORTA SICAKLIK (-15 / +10) MT	T	ÇİFT EVAPORASYON (M + L) TWO EVAP.																				
L	DÜŞÜK SICAKLIK (-15 / - 35) LT	R	ISI GERİ KAZANIM / HEAT RECOVERY																				
	KOMPRESÖR ADET / COMPRESSOR PIECES																						
04 ...	4																						
	KOMPRESÖR MARKA / COMPRESSOR BRAND																						
A	DANFOSS	H	HİTACHI																				
B	BİTZER	I	INVOTECH																				
C	COPELAND	O	BOCK																				
D	DORIN	P	PANASONIC																				
E	EMBRACO	T	TECUMSEH																				
F	FRASCOLD	X	DİĞER																				
	YAĞ KONTROLÜ / LUBRICATING CONTROL																						
E	ELEKTRONİK KONTROL / ELECTRONIC																						
M	MEKANİK KONTROL / MECHANICAL																						
D	YAĞ DENGELEME / OIL BALANCING																						
	SOĞUTMA KAPASİTESİ / COOLING CAPACITY																						
0125	125 KW																						
	SİSTEM KAPASİTE KONTROLÜ / CAPACITY CONTRC																						
S	STANDART																						
I	INVERTER																						
D	DIGITAL KOMPRESÖR																						
	ELEKTRİK BESLEMESİ / ELECTRICAL SUPPLY																						
M	MONOFAZE																						
T	TRİFAZE																						
	FREKANS DEĞERİ / FREQUENCY																						
5	50 Hz																						
6	60 Hz																						
	FAN DEVİR HIZI (RPM) / FAN SPEED																						
6	900	2	440																				
4	1400	1	330																				
3	660	0	FANSIZ																				
	SOĞUTUCU AKIŞKAN / REFRIGERANT																						
G	R404A	F	R407F																				
A	R507A	H	R410A																				
B	R448A-R449A	I	R22																				
C	CO2	K	R134A																				
D	R452A	X	DİĞER																				
E	R407C																						
	FAN KONTROL TİPİ/ FAN CONTROL																						
	STANDART																						
F1	FAN SWITCH / SWITCH																						
F2	FAN KONTROL CİHAZI/ FAN CONTROL DEVICE																						
F3	INVERTER / INVERTER																						
	KONDENSER SICAKLIK FARKI/ ΔT (K)																						
	DT10 (STANDART)																						
DT15	DT15																						
DT12	DT12																						
DT8	DT8																						
	ÖZEL MÜŞTERİ KODU / SPECIAL CUSTOMER CODE																						
	STANDART	MG	MİGROS																				
BM	BİM	CR	CARREFOUR																				
A1	A101	KZ	KAZYON																				
SK	ŞOK	BF	BİM FAS																				

KOMPAKT MERKEZİ SİSTEM - COMPACT CENTRAL SYSTEM

ÜRÜN KOD / PRODUCT CODE	MODEL - MİKTAR / QUANTITY	KAPASİTE / CAPACITY KW	GÜÇ / POWER KW	GRUP ÖLÇÜLERİ / DIMENSIONS EN X BOY X YÜK. / WIDTH X LENGTH X HEIGHT MM	BAĞLANTILAR / CONNECTIONS			FAN / FAN 900 RPM			ELEKTRİK / ELECTRICAL	
					EMİŞ / SUCT. MM	LÜKİT / LIQUID MM	ADET / QTY.	ÇAP / DIA. MM	ADET / QTY.	GÜÇ / POWER KW	VOLTAJ / VOLTAGE	MAK. GÜÇ / MAK. POWER KW
CMC-SM-02B-5,72S-T56B	2HES-2(Y) - (2)	5,72	2,7	610 x 1400 x 1500	22	12	1	450	2	0,33	T5	3,03
CMC-SM-02B-6,76S-T56B	2GES-2(Y) - (2)	6,76	3,2	610 x 1400 x 1500	22	12	1	450	2	0,33	T5	3,53
CMC-SM-02B-8,54S-T56B	2FES-3(Y) - (2)	8,54	4,06	610 x 1400 x 1500	22	12	1	450	2	0,33	T5	4,39
CMC-SM-02B-10,8S-T56B	2EES-3(Y) - (2)	10,8	4,64	610 x 1550 x 1800	28	12	1	450	2	0,33	T5	4,97
CMC-SM-02B-12,5S-T56B	2DES-3(Y) - (2)	12,5	5,42	850 x 1550 x 1900	35	16	1	500	2	0,48	T5	5,9
CMC-SM-02B-15,9S-T56B	2CES-4(Y) - (2)	15,9	6,9	850 x 1550 x 1900	35	16	1	500	2	0,48	T5	7,38
CMC-SM-02B-17,5S-T56B	4FES-5(Y) - (2)	17,5	7,46	1000 x 1750 x 1900	35	16	1	630	2	1,4	T5	8,86
CMC-SM-02B-21,9S-T56B	4EES-6(Y) - (2)	21,9	9,38	1000 x 1750 x 1900	42	16	1	630	2	1,4	T5	10,78
CMC-SM-02B-23,4S-T56B	4EES-6(Y) - (1) + 4DES-7(Y) - (1)	23,4	9,98	1000 x 1750 x 1900	42	18	1	630	2	1,4	T5	11,38
CMC-SM-02B-24,9S-T56B	4DES-7(Y) - (2)	24,9	10,58	1000 x 1750 x 1900	42	18	1	630	2	1,4	T5	11,98
CMC-SM-03B-26,2S-T56B	4FES-5(Y) - (3)	26,2	11,19	850 x 2150 x 1900	42	18	1	500	3	0,72	T5	11,91
CMC-SM-03B-28,4S-T56B	4FES-5(Y) - (2) + 4EES-6(Y) - (1)	28,4	12,15	1000 x 2450 x 1900	54	22	1	630	3	2,1	T5	14,25
CMC-SM-03B-30,6S-T56B	4FES-5(Y) - (1) + 4EES-6(Y) - (2)	30,6	13,11	1000 x 2450 x 1900	54	22	1	630	3	2,1	T5	15,21
CMC-SM-03B-32,9S-T56B	4EES-6(Y) - (3)	32,9	14,07	1000 x 2450 x 1900	54	22	1	630	3	2,1	T5	16,17
CMC-SM-03B-35,9S-T56B	4EES-6(Y) - (1) + 4DES-7(Y) - (2)	35,9	15,27	1000 x 2450 x 1900	54	22	1	630	3	2,1	T5	17,37
CMC-SM-03B-37,4S-T56B	4DES-7(Y) - (3)	37,4	15,87	1000 x 2450 x 1900	54	22	1	630	3	2,1	T5	17,97
CMC-SM-03B-40,9S-T56B	4DES-7(Y) - (2) + 4CES-9(Y) - (1)	40,9	17,4	1000 x 2450 x 1900	54	22	1	630	3	2,1	T5	19,5
CMC-SM-03B-44,4S-T56B	4DES-7(Y) - (1) + 4CES-9(Y) - (2)	44,4	18,93	1000 x 2800 x 2300	66	28	1	630	3	2,1	T5	21,03
CMC-SM-03B-47,8S-T56B	4CES-9(Y) - (3)	47,8	20,46	1000 x 2800 x 2300	66	28	1	630	3	2,1	T5	22,56
CMC-SM-03B-48,9S-T56B	4VES-10(Y) - (3)	48,9	19,77	1000 x 2800 x 2300	66	28	1	630	3	2,1	T5	21,87
CMC-SM-03B-52,5S-T56B	4VES-10(Y) - (2) + 4TES-12(Y) - (1)	52,5	21,3	1000 x 2800 x 2300	66	28	1	630	3	2,1	T5	23,4
CMC-SM-03B-56,1S-T56B	4VES-10(Y) - (1) + 4TES-12(Y) - (2)	56,1	22,83	1100 x 2800 x 2500	66	28	1	800	2	3,88	T5	26,71
CMC-SM-03B-59,6S-T56B	4TES-12(Y) - (3)	59,6	24,36	1100 x 2800 x 2500	66	28	1	800	2	3,88	T5	28,24
CMC-SM-03B-62,2S-T56B	4TES-12(Y) - (2) + 4PES-15(Y) - (1)	62,2	25,38	1100 x 2800 x 2500	54	22	2	800	2	3,88	T5	29,26
CMC-SM-03B-64,7S-T56B	4TES-12(Y) - (1) + 4PES-15(Y) - (2)	64,7	26,4	1100 x 2800 x 2500	54	22	2	800	2	3,88	T5	30,28
CMC-SM-03B-67,2S-T56B	4PES-15(Y) - (3)	67,2	27,42	1100 x 3400 x 2500	54	22	2	800	3	5,82	T5	33,24
CMC-SM-03B-71,9S-T56B	4PES-15(Y) - (2) + 4NES-20(Y) - (1)	71,9	29,1	1100 x 3400 x 2500	54	22	2	800	3	5,82	T5	34,92
CMC-SM-03B-76,6S-T56B	4PES-15(Y) - (1) + 4NES-20(Y) - (2)	76,6	30,78	1100 x 3400 x 2500	54	22	2	800	3	5,82	T5	36,6
CMC-SM-03B-81,3S-T56B	4NES-20(Y) - (3)	81,3	32,46	1100 x 3400 x 2500	66	28	2	800	3	5,82	T5	38,28
CMC-SM-03B-91,8S-T56B	4JE-22(Y) - (3)	91,8	36,87	1100 x 4400 x 2500	66	28	2	800	4	7,76	T5	44,63
CMC-SM-03B-97,5S-T56B	4JE-22(Y) - (2) + 4HE-25(Y) - (1)	97,5	39,24	1100 x 4400 x 2500	66	28	2	800	4	7,76	T5	47
CMC-SM-03B-0103S-T56B	4JE-22(Y) - (1) + 4HE-25(Y) - (2)	103	41,61	1100 x 4400 x 2500	66	28	2	800	4	7,76	T5	49,37

Capacity Values Specified In The Code : Evap. Temp. : -10 °C Condensing Temp. 45 °C : According To EN12900 Subcooling OK, Return Gas 20 °C

- Teknik bilgileri değiştirme hakkımız saklıdır. / We reserve the right to change technical informations.

KOMPAKT MERKEZİ SİSTEM - COMPACT CENTRAL SYSTEM

ÜRÜN KOD / PRODUCT CODE	MODEL - MİKTAR / MODEL - QUANTITY	R448A-R449A KAPASİTE / CAPACITY (Kilowatt) EN12900 (Subcooling OK, Return Gas 20 °C)								
		0°C			-5°C			-10°C		
		45	50	55	45	50	55	45	50	55
CMC-SM-02B-5,72S-T56B	2HES-2(Y) - (2)	8,92	8,08	7,24	7,2	6,48	5,78	5,72	5,12	4,54
CMC-SM-02B-6,76S-T56B	2GES-2(Y) - (2)	10,5	9,5	8,54	8,48	7,64	6,84	6,76	6,06	5,38
CMC-SM-02B-8,54S-T56B	2FES-3(Y) - (2)	13,26	12,02	10,8	10,72	9,68	8,68	8,54	7,68	6,82
CMC-SM-02B-10,8S-T56B	2EES-3(Y) - (2)	16,58	15,26	13,9	13,44	12,32	11,18	10,76	9,8	8,84
CMC-SM-02B-12,5S-T56B	2DES-3(Y) - (2)	19,22	17,7	16,16	15,6	14,32	13,02	12,5	11,42	10,34
CMC-SM-02B-15,9S-T56B	2CES-4(Y) - (2)	24,36	22,48	20,58	19,84	18,24	16,66	15,96	14,64	13,3
CMC-SM-02B-17,5S-T56B	4FES-5(Y) - (2)	26,84	24,72	22,58	21,8	20	18,22	17,48	16	14,5
CMC-SM-02B-21,9S-T56B	4EES-6(Y) - (2)	33,68	31	28,32	27,32	25,08	22,82	21,9	20,02	18,14
CMC-SM-02B-23,4S-T56B	4EES-6(Y) - (1) + 4DES-7(Y) - (1)	36,07	33,19	30,31	29,25	26,84	24,41	23,43	21,41	19,39
CMC-SM-02B-24,9S-T56B	4DES-7(Y) - (2)	38,46	35,38	32,3	31,18	28,6	26	24,96	22,8	20,64
CMC-SM-03B-26,2S-T56B	4FES-5(Y) - (3)	40,26	37,08	33,87	32,7	30	27,33	26,22	24	21,75
CMC-SM-03B-28,4S-T56B	4FES-5(Y) - (2) + 4EES-6(Y) - (1)	43,68	40,22	36,74	35,46	32,54	29,63	28,43	26,01	23,57
CMC-SM-03B-30,6S-T56B	4FES-5(Y) - (1) + 4EES-6(Y) - (2)	47,1	43,36	39,61	38,22	35,08	31,93	30,64	28,02	25,39
CMC-SM-03B-32,9S-T56B	4EES-6(Y) - (3)	50,52	46,5	42,48	40,98	37,62	34,23	32,85	30,03	27,21
CMC-SM-03B-35,9S-T56B	4EES-6(Y) - (1) + 4DES-7(Y) - (2)	55,3	50,88	46,46	44,84	41,14	37,41	35,91	32,81	29,71
CMC-SM-03B-37,4S-T56B	4DES-7(Y) - (3)	57,69	53,07	48,45	46,77	42,9	39	37,44	34,2	30,96
CMC-SM-03B-40,9S-T56B	4DES-7(Y) - (2) + 4CES-9(Y) - (1)	62,86	57,88	52,9	51,01	46,84	42,65	40,9	37,41	33,93
CMC-SM-03B-44,4S-T56B	4DES-7(Y) - (1) + 4CES-9(Y) - (2)	68,03	62,69	57,35	55,25	50,78	46,3	44,36	40,62	36,9
CMC-SM-03B-47,8S-T56B	4CES-9(Y) - (3)	73,2	67,5	61,8	59,49	54,72	49,95	47,82	43,83	39,87
CMC-SM-03B-48,9S-T56B	4VES-10(Y) - (3)	76,5	69,9	63,6	61,5	56,13	50,7	48,96	44,37	39,87
CMC-SM-03B-52,5S-T56B	4VES-10(Y) - (2) + 4TES-12(Y) - (1)	81,8	74,9	68,1	65,9	60,22	54,5	52,53	47,69	42,93
CMC-SM-03B-56,1S-T56B	4VES-10(Y) - (1) + 4TES-12(Y) - (2)	87,1	79,9	72,6	70,3	64,31	58,3	56,1	51,01	45,99
CMC-SM-03B-59,6S-T56B	4TES-12(Y) - (3)	92,4	84,9	77,1	74,7	68,4	62,1	59,67	54,33	49,05
CMC-SM-03B-62,2S-T56B	4TES-12(Y) - (2) + 4PES-15(Y) - (1)	96,8	88,8	80,5	78,1	71,3	64,6	62,18	56,52	50,85
CMC-SM-03B-64,7S-T56B	4TES-12(Y) - (1) + 4PES-15(Y) - (2)	101,2	92,7	83,9	81,5	74,2	67,1	64,69	58,71	52,65
CMC-SM-03B-67,2S-T56B	4PES-15(Y) - (3)	105,6	96,6	87,3	84,9	77,1	69,6	67,2	60,9	54,45
CMC-SM-03B-71,9S-T56B	4PES-15(Y) - (2) + 4NES-20(Y) - (1)	112,5	103	93,3	90,6	82,5	74,6	71,9	65,3	58,6
CMC-SM-03B-76,6S-T56B	4PES-15(Y) - (1) + 4NES-20(Y) - (2)	119,4	109,4	99,3	96,3	87,9	79,6	76,6	69,7	62,75
CMC-SM-03B-81,3S-T56B	4NES-20(Y) - (3)	126,3	115,8	105,3	102	93,3	84,6	81,3	74,1	66,9
CMC-SM-03B-91,8S-T56B	4JE-22(Y) - (3)	141	129,3	117,9	114,6	104,7	95,1	91,8	83,7	75,3
CMC-SM-03B-97,5S-T56B	4JE-22(Y) - (2) + 4HE-25(Y) - (1)	149,2	136,9	124,8	121,4	111,1	100,9	97,5	89	80,2
CMC-SM-03B-0103S-T56B	4JE-22(Y) - (1) + 4HE-25(Y) - (2)	157,4	144,5	131,7	128,2	117,5	106,7	103,2	94,3	85,1

KOMPAKT MERKEZİ SİSTEM - COMPACT CENTRAL SYSTEM

ÜRÜN KOD / PRODUCT CODE	MODEL - MİKTAR / QUANTITY	KAPASİTE / CAPACITY KW	GÜÇ / POWER KW	GRUP ÖLÇÜLERİ / DIMENSIONS EN X BOY X YÜK. / WIDTH X LENGTH X HEIGHT MM	BAĞLANTILAR / CONNECTIONS			FAN / FAN 900 RPM		ELEKTRİK / ELECTRICAL		
					EMİŞ / SUCT. MM	LİKİT / LIQUID MM	ADET / QTY.	ÇAP / DIA. MM	ADET / QTY.	GÜÇ / POWER KW	VOLTAJ / VOLTAGE	MAK. GÜÇ MAX. POWER KW
CMC-SM-02D-5,10S-T56B	H 101 CC - (2)	5,1	2,48	610 x 1400 x 1500	22	12	1	450	2	0,33	T5	2,81
CMC-SM-02D-6,10S-T56B	H 151 CC - (2)	6,08	2,92	610 x 1400 x 1500	22	12	1	450	2	0,33	T5	3,25
CMC-SM-02D-6,70S-T56B	H 181 CC - (2)	6,68	3,38	610 x 1400 x 1500	22	12	1	450	2	0,33	T5	3,71
CMC-SM-02D-8,60S-T56B	H 201 CC - (2)	8,56	4,08	610 x 1400 x 1500	28	12	1	450	2	0,33	T5	4,41
CMC-SM-02D-9,10S-T56B	H 221 CC - (2)	9,1	4,28	610 x 1400 x 1500	28	12	1	450	2	0,33	T5	4,61
CMC-SM-02D-9,90S-T56B	H 251 CC - (2)	9,98	4,7	610 x 1400 x 1500	28	12	1	450	2	0,33	T5	5,03
CMC-SM-02D-10,8S-T56B	H 281 CC - (2)	10,84	5,36	610 x 1400 x 1500	28	12	1	500	2	0,48	T5	5,84
CMC-SM-02D-13,9S-T56B	H 300 CC - (2)	13,92	6,32	610 x 1400 x 1500	35	16	1	500	2	0,48	T5	6,8
CMC-SM-02D-15,6S-T56B	H 350 CC - (2)	15,62	6,86	610 x 1400 x 1500	35	16	1	500	2	0,48	T5	7,34
CMC-SM-02D-17,4S-T56B	H 380 CC - (2)	17,42	7,88	610 x 1550 x 1800	42	16	1	500	2	0,48	T5	8,36
CMC-SM-02D-18,4S-T56B	H 405 CC - (2)	18,42	8,14	1000 x 1750 x 1900	42	16	1	630	2	1,4	T5	9,54
CMC-SM-02D-22,3S-T56B	H 505 CC - (2)	22,32	9,68	1000 x 1750 x 1900	42	18	1	630	2	1,4	T5	11,08
CMC-SM-02D-25,5S-T56B	H 701 CC - (2)	25,52	10,9	1000 x 1750 x 1900	42	18	1	630	2	1,4	T5	12,3
CMC-SM-03D-26,1S-T56B	H 380 CC - (3)	26,13	11,82	850 x 2150 x 1900	54	22	1	500	3	0,72	T5	12,54
CMC-SM-03D-27,6S-T56B	H 405 CC - (3)	27,63	12,21	1000 x 2450 x 1900	54	22	1	630	3	2,1	T5	14,31
CMC-SM-03D-29,6S-T56B	H 405 CC - (2) + H 505 CC - (1)	29,58	12,98	1000 x 2450 x 1900	54	22	1	630	3	2,1	T5	15,08
CMC-SM-03D-33,5S-T56B	H 505 CC - (3)	33,48	14,52	1000 x 2450 x 1900	54	22	1	630	3	2,1	T5	16,62
CMC-SM-03D-35,5S-T56B	H 505 CC - (2) + H 705 CC - (1)	35,45	15,29	1000 x 2450 x 1900	54	22	1	630	3	2,1	T5	17,39
CMC-SM-03D-37,4S-T56B	H 505 CC - (1) + H 705 CC - (2)	37,42	16,06	1000 x 2450 x 1900	54	22	1	630	3	2,1	T5	18,16
CMC-SM-03D-39,4S-T56B	H 705 CC - (3)	39,39	16,83	1000 x 2450 x 1900	54	22	1	630	3	2,1	T5	18,93
CMC-SM-03D-43,7S-T56B	H 751 CC - (3)	43,68	18,51	1000 x 2800 x 2300	66	28	1	630	3	2,1	T5	20,61
CMC-SM-03D-46,4S-T56B	H 755 CC - (3)	46,35	19,71	1000 x 2800 x 2300	66	28	1	630	3	2,1	T5	21,81
CMC-SM-03D-47,0S-T56B	H 751 CC - (2) + H 1002 CC - (1)	46,97	19,85	1000 x 2800 x 2300	66	28	1	630	3	2,1	T5	21,95
CMC-SM-03D-50,3S-T56B	H 751 CC - (1) + H 1002 CC - (2)	50,26	21,19	1000 x 2800 x 2300	66	28	1	630	3	2,1	T5	23,29
CMC-SM-03D-51,2S-T56B	H 755 CC - (1) + H 1002 CC - (2)	51,15	21,59	1000 x 2800 x 2300	66	28	1	630	3	2,1	T5	23,69
CMC-SM-03D-53,6S-T56B	H 1002 CC - (3)	53,55	22,53	1100 x 2800 x 2500	66	28	1	800	2	3,88	T5	26,41
CMC-SM-03D-55,8S-T56B	H 1002 CC - (2) + H 1003 CC - (1)	55,75	23,71	1100 x 2800 x 2500	66	28	1	800	2	3,88	T5	27,59
CMC-SM-03D-57,9S-T56B	H 1002 CC - (1) + H 1003 CC - (2)	57,95	24,89	1100 x 2800 x 2500	66	28	1	800	2	3,88	T5	28,77
CMC-SM-03D-60,2S-T56B	H 1003 CC - (3)	60,15	26,07	1100 x 2800 x 2500	66	28	1	800	2	3,88	T5	29,95
CMC-SM-03D-63,9S-T56B	H 1201 CC - (3)	63,87	26,04	1100 x 2800 x 2500	54	22	2	800	2	3,88	T5	29,92
CMC-SM-03D-67,3S-T56B	H 1201 CC - (2) + H 1501 CC - (1)	67,26	27,51	1100 x 3400 x 2500	54	22	2	800	3	5,82	T5	33,33
CMC-SM-03D-70,7S-T56B	H 1201 CC - (1) + H 1501 CC - (2)	70,65	28,98	1100 x 3400 x 2500	54	22	2	800	3	5,82	T5	34,8
CMC-SM-03D-74,1S-T56B	H 1501 CC - (3)	74,04	30,45	1100 x 3400 x 2500	54	22	2	800	3	5,82	T5	36,27
CMC-SM-03D-78,1S-T56B	H 1501 CC - (2) + H 2001 CC - (1)	78,09	32,18	1100 x 3400 x 2500	54	22	2	800	3	5,82	T5	38
CMC-SM-03D-82,1S-T56B	H 1501 CC - (1) + H 2001 CC - (2)	82,14	33,91	1100 x 3400 x 2500	66	28	2	800	3	5,82	T5	39,73
CMC-SM-03D-86,2S-T56B	H 2001 CC - (3)	86,19	35,64	1100 x 3400 x 2500	66	28	2	800	3	5,82	T5	41,46
CMC-SM-03D-89,9S-T56B	H 2001 CC - (2) + H 2201 CC - (1)	89,87	37	1100 x 4400 x 2500	66	28	2	800	4	7,76	T5	44,76
CMC-SM-03D-93,6S-T56B	H 2001 CC - (1) + H 2201 CC - (2)	93,55	38,36	1100 x 4400 x 2500	66	28	2	800	4	7,76	T5	46,12
CMC-SM-03D-97,2S-T56B	H 2201 CC - (3)	97,23	39,72	1100 x 4400 x 2500	66	28	2	800	4	7,76	T5	47,48
CMC-SM-03D-0100S-T56B	H 2201 CC - (2) + H 2401 CC - (1)	100,38	41,22	1100 x 4400 x 2500	66	28	2	800	4	7,76	T5	48,98
CMC-SM-03D-0104S-T56B	H 2201 CC - (1) + H 2401 CC - (2)	103,53	72,72	1100 x 4400 x 2500	66	28	2	800	4	7,76	T5	80,48

Capacity Values Specified In The Code : Evap. Temp. : -10 °C Condensing Temp. 45 °C . According To EN12900 Subcooling OK, Return Gas 20 °C

- Teknik bilgileri değiştirme hakkımız saklıdır. / We reserve the right to change technical informations.

KOMPAKT MERKEZİ SİSTEM - COMPACT CENTRAL SYSTEM

ÜRÜN KOD / PRODUCT CODE	MODEL - MİKTAR / MODEL - QUANTITY	R448A-R449A KAPASİTE / CAPACITY (Kilowatt) EN12900 (Subcooling OK, Return Gas 20 °C)								
		0°C			-5°C			-10°C		
		45	50	55	45	50	55	45	50	55
CMC-SM-02D-5,10S-T56B	H 101 CC - (2)	7,88	7,28	N/A	6,38	5,84	5,32	5,1	4,64	4,22
CMC-SM-02D-6,10S-T56B	H 151 CC - (2)	9,32	8,52	N/A	7,56	6,88	6,2	6,08	5,5	4,94
CMC-SM-02D-6,70S-T56B	H 181 CC - (2)	10,24	9,36	8,52	8,32	7,58	6,86	6,68	6,06	5,44
CMC-SM-02D-8,60S-T56B	H 201 CC - (2)	13,1	12,04	10,98	10,66	9,74	8,82	8,56	7,78	7
CMC-SM-02D-9,10S-T56B	H 221 CC - (2)	13,96	12,76	11,6	11,34	10,34	9,34	9,1	8,26	7,44
CMC-SM-02D-9,90S-T56B	H 251 CC - (2)	15,18	13,92	12,7	12,38	11,32	10,3	9,98	9,1	8,26
CMC-SM-02D-10,8S-T56B	H 281 CC - (2)	16,68	15,36	14,04	13,54	12,4	11,28	10,84	9,88	8,94
CMC-SM-02D-13,9S-T56B	H 300 CC - (2)	21,26	19,56	17,86	17,3	15,84	14,42	13,92	12,7	11,5
CMC-SM-02D-15,6S-T56B	H 350 CC - (2)	23,62	21,78	19,94	19,32	17,74	16,16	15,62	14,28	12,96
CMC-SM-02D-17,4S-T56B	H 380 CC - (2)	26,26	24,24	N/A	21,5	19,78	18,06	17,42	15,96	14,52
CMC-SM-02D-18,4S-T56B	H 405 CC - (2)	28,18	25,98	23,82	22,92	21,06	19,24	18,42	16,86	15,36
CMC-SM-02D-22,3S-T56B	H 505 CC - (2)	34,22	31,64	29,1	27,8	25,64	23,5	22,32	20,52	18,78
CMC-SM-02D-25,5S-T56B	H 701 CC - (2)	39,04	35,9	32,84	31,76	29,12	26,56	25,52	23,34	21,26
CMC-SM-03D-26,1S-T56B	H 380 CC - (3)	39,39	36,36	N/A	32,25	29,67	27,09	26,13	23,94	21,78
CMC-SM-03D-27,6S-T56B	H 405 CC - (3)	42,27	38,97	35,73	34,38	31,59	28,86	27,63	25,29	23,04
CMC-SM-03D-29,6S-T56B	H 405 CC - (2) + H 505 CC - (1)	45,29	41,8	38,37	36,82	33,88	30,99	29,58	27,12	24,75
CMC-SM-03D-33,5S-T56B	H 505 CC - (3)	51,33	47,46	43,65	41,7	38,46	35,25	33,48	30,78	28,17
CMC-SM-03D-35,5S-T56B	H 505 CC - (2) + H 705 CC - (1)	54,27	50,14	46,07	44,12	40,65	37,23	35,45	32,56	29,76
CMC-SM-03D-37,4S-T56B	H 505 CC - (1) + H 705 CC - (2)	57,21	52,82	48,49	46,54	42,84	39,21	37,42	34,34	31,35
CMC-SM-03D-39,4S-T56B	H 705 CC - (3)	60,15	55,5	50,91	48,96	45,03	41,19	39,39	36,12	32,94
CMC-SM-03D-43,7S-T56B	H 751 CC - (3)	66,87	61,47	56,22	54,36	49,83	45,45	43,68	39,93	36,36
CMC-SM-03D-46,4S-T56B	H 755 CC - (3)	70,65	65,43	60,3	57,51	53,16	48,93	46,35	42,81	39,36
CMC-SM-03D-47,0S-T56B	H 751 CC - (2) + H 1002 CC - (1)	71,89	66,11	60,5	58,45	53,61	48,93	46,97	42,97	39,15
CMC-SM-03D-50,3S-T56B	H 751 CC - (1) + H 1002 CC - (2)	76,91	70,75	64,78	62,54	57,39	52,41	50,26	46,01	41,94
CMC-SM-03D-51,2S-T56B	H 755 CC - (1) + H 1002 CC - (2)	78,17	72,07	66,14	63,59	58,5	53,57	51,15	46,97	42,94
CMC-SM-03D-53,6S-T56B	H 1002 CC - (3)	81,93	75,39	69,06	66,63	61,17	55,89	53,55	49,05	44,73
CMC-SM-03D-55,8S-T56B	H 1002 CC - (2) + H 1003 CC - (1)	85,94	79,05	72,36	69,91	64,15	58,57	56,2	51,45	46,88
CMC-SM-03D-57,9S-T56B	H 1002 CC - (1) + H 1003 CC - (2)	89,95	82,71	75,66	73,19	67,13	61,25	58,85	53,85	49,03
CMC-SM-03D-60,2S-T56B	H 1003 CC - (3)	93,96	86,37	78,96	76,47	70,11	63,93	61,5	56,25	51,18
CMC-SM-03D-63,9S-T56B	H 1201 CC - (3)	97,29	90,06	82,86	79,32	73,14	67,02	63,87	58,68	53,52
CMC-SM-03D-67,3S-T56B	H 1201 CC - (2) + H 1501 CC - (1)	102,31	94,7	87,11	83,46	76,95	70,48	67,26	61,77	56,3
CMC-SM-03D-70,7S-T56B	H 1201 CC - (1) + H 1501 CC - (2)	107,33	99,34	91,36	87,6	80,76	73,94	70,65	64,86	59,08
CMC-SM-03D-74,1S-T56B	H 1501 CC - (3)	112,35	103,98	95,61	91,74	84,57	77,4	74,04	67,95	61,86
CMC-SM-03D-78,1S-T56B	H 1501 CC - (2) + H 2001 CC - (1)	118,48	109,69	100,89	96,74	89,23	81,7	78,09	71,72	65,33
CMC-SM-03D-82,1S-T56B	H 1501 CC - (1) + H 2001 CC - (2)	124,61	115,4	106,17	101,74	93,89	86	82,14	75,49	68,8
CMC-SM-03D-86,2S-T56B	H 2001 CC - (3)	130,74	121,11	111,45	106,74	98,55	90,3	86,19	79,26	72,27
CMC-SM-03D-89,9S-T56B	H 2001 CC - (2) + H 2201 CC - (1)	136,06	126,07	116,07	111,04	102,53	93,99	89,6	82,41	75,19
CMC-SM-03D-93,6S-T56B	H 2001 CC - (1) + H 2201 CC - (2)	141,38	131,03	120,69	115,34	106,51	97,68	93,01	85,56	78,11
CMC-SM-03D-97,2S-T56B	H 2201 CC - (3)	146,7	135,99	125,31	119,64	110,49	101,37	96,42	88,71	81,03
CMC-SM-03D-0100S-T56B	H 2201 CC - (2) + H 2401 CC - (1)	151,91	140,82	129,76	123,89	114,41	104,97	99,84	91,86	80,91
CMC-SM-03D-0104S-T56B	H 2201 CC - (1) + H 2401 CC - (2)	157,12	145,65	134,21	128,14	118,33	108,57	103,26	95,01	80,79

KOMPAKT MERKEZİ SİSTEM - COMPACT CENTRAL SYSTEM

ÜRÜN KOD / PRODUCT CODE	MODEL - MİKTAR / QUANTITY	KAPASİTE / CAPACITY KW	GÜÇ / POWER KW	GRUP ÖLÇÜLERİ / DIMENSIONS EN X BOY X YÜKS. / WIDTH X LENGTH X HEIGHT MM	BAĞLANTILAR / CONNECTIONS			FAN / FAN 900 RPM			ELEKTRİK / ELECTRICAL	
					EMİŞ / SUCTION MM	LİKİT / LIQUID MM	ADET / QTY.	ÇAP / DIA. MM	ADET / QTY.	GÜÇ / POWER KW	VOLTAJ / VOLTAGE	MAK. GÜÇ MAX. POWER KW
CMC-SM-02F-4,66S-T56B	A1-6Y - (2)	4,66	2,26	610 x 1550 x 1800	22	12	1	450	2	0,33	T5	2,59
CMC-SM-02F-6,80S-T56B	A1-5-8Y - (2)	6,8	3,26	610 x 1550 x 1800	22	12	1	450	2	0,33	T5	3,59
CMC-SM-02F-8,84S-T56B	B2-10.1Y - (2)	8,84	4,16	610 x 1550 x 1800	28	12	1	450	2	0,33	T5	4,49
CMC-SM-02F-10,7S-T56B	D2-11.1Y - (2)	10,72	4,68	610 x 1550 x 1800	28	12	1	450	2	0,33	T5	5,01
CMC-SM-02F-12,7S-T56B	D3-13.1Y - (2)	12,68	5,54	610 x 1550 x 1800	35	16	1	500	2	0,48	T5	6,02
CMC-SM-02F-14,7S-T56B	D3-15.1Y - (2)	14,74	6,38	610 x 1550 x 1800	35	16	1	500	2	0,48	T5	6,86
CMC-SM-02F-16,1S-T56B	D4-16.1Y - (2)	16,08	6,98	850 x 1550 x 1900	35	16	1	500	2	0,48	T5	7,46
CMC-SM-02F-17,5S-T56B	D4-18.1Y - (2)	17,5	7,6	850 x 1550 x 1900	42	16	1	500	2	0,48	T5	8,08
CMC-SM-02F-20,2S-T56B	Q5-21.1Y - (2)	20,24	8,68	1000 x 1750 x 1900	42	16	1	630	2	1,4	T5	10,08
CMC-SM-02F-23,0S-T56B	Q5-24.1Y - (2)	23,02	9,82	1000 x 1750 x 1900	42	18	1	630	2	1,4	T5	11,22
CMC-SM-02F-23,7S-T56B	Q5-25.1Y - (2)	23,74	10,12	1000 x 1750 x 1900	42	18	1	630	2	1,4	T5	11,52
CMC-SM-03F-26,3S-T56B	D4-18.1Y - (3)	26,25	11,4	850 x 2150 x 1900	54	22	1	500	3	0,72	T5	12,12
CMC-SM-03F-30,4S-T56B	Q5-21.1Y - (3)	30,36	13,02	1000 x 2450 x 1900	54	22	1	630	3	2,1	T5	15,12
CMC-SM-03F-31,8S-T56B	Q5-21.1Y - (2) + Q5-24.1Y - (1)	31,75	13,59	1000 x 2450 x 1900	54	22	1	630	3	2,1	T5	15,69
CMC-SM-03F-34,5S-T56B	Q5-24.1Y - (3)	34,53	14,73	1000 x 2450 x 1900	54	22	1	630	3	2,1	T5	16,83
CMC-SM-03F-35,6S-T56B	Q5-25.1Y - (3)	35,61	15,18	1000 x 2450 x 1900	54	22	1	630	3	2,1	T5	17,28
CMC-SM-03F-38,8S-T56B	Q5-25.1Y - (1) + Q7-28.1Y - (2)	38,75	16,46	1000 x 2450 x 1900	54	22	1	630	3	2,1	T5	18,56
CMC-SM-03F-40,3S-T56B	Q7-28.1Y - (3)	40,32	17,1	1000 x 2450 x 1900	66	28	1	630	3	2,1	T5	19,2
CMC-SM-03F-42,9S-T56B	Q7-28.1Y - (2) + Q7-33.1Y - (1)	42,95	18,23	1000 x 2800 x 2300	66	28	1	630	3	2,1	T5	20,33
CMC-SM-03F-45,6S-T56B	Q7-28.1Y - (1) + Q7-33.1Y - (2)	45,58	19,36	1000 x 2800 x 2300	66	28	1	630	3	2,1	T5	21,46
CMC-SM-03F-48,2S-T56B	Q7-33.1Y - (3)	48,21	20,49	1000 x 2800 x 2300	66	28	1	630	3	2,1	T5	22,59
CMC-SM-03F-59,2S-T56B	S12-42Y - (3)	59,19	24,36	1100 x 2800 x 2500	66	28	1	800	2	3,88	T5	28,24
CMC-SM-03F-63,2S-T56B	S12-42Y - (2) + S15-52Y - (1)	63,17	26,02	1100 x 2800 x 2500	54	22	2	800	2	3,88	T5	29,9
CMC-SM-03F-67,2S-T56B	S12-42Y - (1) + S15-52Y - (2)	67,15	27,68	1100 x 3400 x 2500	54	22	2	800	3	5,82	T5	33,5
CMC-SM-03F-71,1S-T56B	S15-52Y - (3)	71,13	29,34	1100 x 3400 x 2500	54	22	2	800	3	5,82	T5	35,16
CMC-SM-03F-74,5S-T56B	S15-52Y - (2) + S20-56Y - (1)	74,52	30,44	1100 x 3400 x 2500	54	22	2	800	3	5,82	T5	36,26
CMC-SM-03F-77,9S-T56B	S15-52Y - (1) + S20-56Y - (2)	77,91	31,54	1100 x 3400 x 2500	66	28	2	800	3	5,82	T5	37,36
CMC-SM-03F-81,3S-T56B	S20-56Y - (3)	81,3	32,64	1100 x 3400 x 2500	66	28	2	800	3	5,82	T5	38,46
CMC-SM-03F-0104S-T56B	V25-71Y - (3)	104,37	41,88	1100 x 4400 x 2500	66	28	2	800	4	7,76	T5	49,64

Capacity Values Specified In The Code : Evap. Temp. : -10 °C Condensing Temp. 45 °C . According To EN12900 Subcooling OK, Return Gas 20 °C

- Teknik bilgileri değiştirme hakkımız saklıdır. / We reserve the right to change technical informations.

KOMPAKT MERKEZİ SİSTEM - COMPACT CENTRAL SYSTEM

ÜRÜN KOD / PRODUCT CODE	MODEL - MİKTAR / MODEL - QUANTITY	R448A-R449A KAPASİTE / CAPACITY (Kilowatt) EN12900 (Subcooling OK, Return Gas 20 °C)								
		0°C			-5°C			-10°C		
		45	50	55	45	50	55	45	50	55
CMC-SM-02F-4,66S-T56B	A1-6Y - (2)	7,34	6,62	5,9	5,9	5,3	4,7	4,66	4,16	3,66
CMC-SM-02F-6,80S-T56B	A1.5-8Y - (2)	10,58	9,58	N/A	8,54	7,7	6,86	6,8	6,12	5,42
CMC-SM-02F-8,84S-T56B	B2-10.IY - (2)	13,72	12,46	11,18	11,1	10,04	8,98	8,84	7,98	7,08
CMC-SM-02F-10,7S-T56B	D2-11.IY - (2)	16,52	15,22	13,9	13,4	12,28	11,16	10,72	9,76	8,82
CMC-SM-02F-12,7S-T56B	D3-13.IY - (2)	19,48	17,9	16,3	15,8	14,46	13,12	12,68	11,56	10,42
CMC-SM-02F-14,7S-T56B	D3-15.IY - (2)	22,68	20,86	19,02	18,38	16,84	15,3	14,74	13,44	12,14
CMC-SM-02F-16,1S-T56B	D4-16.IY - (2)	24,66	22,72	20,82	20,02	18,38	16,76	16,08	14,72	13,36
CMC-SM-02F-17,5S-T56B	D4-18.IY - (2)	26,76	24,68	22,64	21,76	20	18,26	17,5	16,04	14,58
CMC-SM-02F-20,2S-T56B	Q5-21.IY - (2)	31,26	28,74	26,28	25,28	23,16	21,08	20,24	18,46	16,74
CMC-SM-02F-23,0S-T56B	Q5-24.IY - (2)	35,48	32,58	29,66	28,76	26,28	23,82	23,02	20,98	18,92
CMC-SM-02F-23,7S-T56B	Q5-25.IY - (2)	36,54	33,56	30,56	29,62	27,08	24,56	23,74	21,62	19,5
CMC-SM-03F-26,3S-T56B	D4-18.IY - (3)	40,14	37,02	33,96	32,64	30	27,39	26,25	24,06	21,87
CMC-SM-03F-30,4S-T56B	Q5-21.IY - (3)	46,89	43,11	39,42	37,92	34,74	31,62	30,36	27,69	25,11
CMC-SM-03F-31,8S-T56B	Q5-21.IY - (2) + Q5-24.IY - (1)	49	45,03	41,11	39,66	36,3	32,99	31,75	28,95	26,2
CMC-SM-03F-34,5S-T56B	Q5-24.IY - (3)	53,22	48,87	44,49	43,14	39,42	35,73	34,53	31,47	28,38
CMC-SM-03F-35,6S-T56B	Q5-25.IY - (3)	54,81	50,34	45,84	44,43	40,62	36,84	35,61	32,43	29,25
CMC-SM-03F-38,8S-T56B	Q5-25.IY - (1) + Q7-28.IY - (2)	59,71	54,86	49,96	48,37	44,24	40,1	38,75	35,29	31,81
CMC-SM-03F-40,3S-T56B	Q7-28.IY - (3)	62,16	57,12	52,02	50,34	46,05	41,73	40,32	36,72	33,09
CMC-SM-03F-42,9S-T56B	Q7-28.IY - (2) + Q7-33.IY - (1)	66,03	60,71	55,33	53,54	49,03	44,47	42,95	39,17	35,35
CMC-SM-03F-45,6S-T56B	Q7-28.IY - (1) + Q7-33.IY - (2)	69,9	64,3	58,64	56,74	52,01	47,21	45,58	41,62	37,61
CMC-SM-03F-48,2S-T56B	Q7-33.IY - (3)	73,77	67,89	61,95	59,94	54,99	49,95	48,21	44,07	39,87
CMC-SM-03F-59,2S-T56B	S12-42Y - (3)	91,98	84,42	76,92	74,19	67,83	61,56	59,19	53,91	48,69
CMC-SM-03F-63,2S-T56B	S12-42Y - (2) + S15-52Y - (1)	98,62	90,26	81,95	79,39	72,36	65,39	63,17	57,33	51,54
CMC-SM-03F-67,2S-T56B	S12-42Y - (1) + S15-52Y - (2)	105,26	96,1	86,98	84,59	76,89	69,22	67,15	60,75	54,39
CMC-SM-03F-71,1S-T56B	S15-52Y - (3)	111,9	101,94	92,01	89,79	81,42	73,05	71,13	64,17	57,24
CMC-SM-03F-74,5S-T56B	S15-52Y - (2) + S20-56Y - (1)	116,63	106,44	96,27	93,8	85,23	76,66	74,52	67,39	60,28
CMC-SM-03F-77,9S-T56B	S15-52Y - (1) + S20-56Y - (2)	121,36	110,94	100,53	97,81	89,04	80,27	77,91	70,61	63,32
CMC-SM-03F-81,3S-T56B	S20-56Y - (3)	126,09	115,44	104,79	101,82	92,85	83,88	81,3	73,83	66,36
CMC-SM-03F-0104S-T56B	V25-71Y - (3)	159,09	146,19	133,14	129,57	118,65	107,61	104,37	95,22	85,98

KOMPAKT MERKEZİ SİSTEM - COMPACT CENTRAL SYSTEM

ÜRÜN KOD / PRODUCT CODE	MODEL - MİKTAR / QUANTITY	KAPASİTE / CAPACITY KW	GÜÇ / POWER KW	GRUP ÖLÇÜLERİ / DIMENSIONS EN X BOY X YÜKS. / WIDTH X LENGTH X HEIGHT MM	BAĞLANTILAR / CONNECTIONS			FAN / FAN 900 RPM			ELEKTRİK / ELECTRICAL	
					EMİŞ / SUCT. MM	LİKİT / LIQUID MM	ADET / QTY.	ÇAP / DIA. MM	ADET / QTY.	GÜÇ / POWER KW	VOLTAJ / VOLTAGE	MAK. GÜÇ MAK. POWER KW
CMC-CM-02C-6,60S-T56B	ZB15KCE - (2)	6,6	3,36	610 x 1400 x 1500	28	12	1	450	2	0,33	T5	3,69
CMC-CM-02C-7,66S-T56B	ZB19KCE - (2)	7,66	3,68	610 x 1400 x 1500	28	12	1	450	2	0,33	T5	4,01
CMC-CM-02C-9,74S-T56B	ZB21KCE - (2)	9,74	4,68	610 x 1400 x 1500	28	12	1	500	2	0,48	T5	5,16
CMC-CM-02C-11,1S-T56B	ZB26KCE - (2)	11,02	5,38	610 x 1400 x 1500	28	12	1	500	2	0,48	T5	5,86
CMC-CM-02C-12,9S-T56B	ZB29KCE - (2)	12,86	5,98	610 x 1400 x 1500	28	12	1	500	2	0,48	T5	6,46
CMC-CM-02C-16,7S-T56B	ZB38KCE - (2)	16,68	7,74	610 x 1550 x 1800	35	16	1	500	2	0,48	T5	8,22
CMC-CM-02C-18,1S-T56B	ZB38KCE - (1) + ZB 45 KCE - (1)	18,11	8,25	610 x 1550 x 1800	35	16	1	500	2	0,48	T5	8,73
CMC-CM-02C-19,5S-T56B	ZB45KCE - (2)	19,54	8,76	1000 x 1750 x 1900	35	16	1	630	2	1,4	T5	10,16
CMC-CM-02C-20,6S-T56B	ZB45KCE - (1) + ZB 48 KCE - (1)	20,62	9,25	1000 x 1750 x 1900	42	16	1	630	2	1,4	T5	10,65
CMC-CM-02C-21,7S-T56B	ZB48KCE - (2)	21,7	9,74	1000 x 1750 x 1900	42	18	1	630	2	1,4	T5	11,14
CMC-CM-03C-25,1S-T56B	ZB38KCE - (3)	25,02	11,61	1000 x 1750 x 1900	42	18	1	630	2	1,4	T5	13,01
CMC-CM-03C-26,5S-T56B	ZB38KCE - (2) + ZB 45 KCE - (1)	26,45	12,12	1000 x 1750 x 1900	42	18	1	630	2	1,4	T5	13,52
CMC-CM-03C-29,3S-T56B	ZB45KCE - (3)	29,31	13,14	1000 x 2450 x 1900	42	18	1	630	3	2,1	T5	15,24
CMC-CM-03C-30,4S-T56B	ZB45KCE - (2) + ZB 48 KCE - (1)	30,39	13,63	1000 x 2450 x 1900	42	18	1	630	3	2,1	T5	15,73
CMC-CM-03C-31,5S-T56B	ZB45KCE - (1) + ZB 48 KCE - (2)	31,47	14,12	1000 x 2450 x 1900	54	22	1	630	3	2,1	T5	16,22
CMC-CM-03C-32,6S-T56B	ZB48KCE - (3)	32,55	14,61	1000 x 2450 x 1900	54	22	1	630	3	2,1	T5	16,71
CMC-CM-03C-34,2S-T56B	ZB48KCE - (2) + ZB 57 KCE - (1)	34,2	15,21	1000 x 2450 x 1900	54	22	1	630	3	2,1	T5	17,31
CMC-CM-03C-37,5S-T56B	ZB57KCE - (3)	37,5	16,41	1000 x 2450 x 1900	54	22	1	630	3	2,1	T5	18,51
CMC-CM-03C-43,9S-T56B	ZB66K5E - (3)	43,95	19,53	1000 x 2800 x 2300	54	22	1	630	3	2,1	T5	21,63
CMC-CM-03C-46,6S-T56B	ZB66K5E - (2) + ZB 76 K5E - (1)	46,6	20,48	1000 x 2800 x 2300	54	22	1	630	3	2,1	T5	22,58
CMC-CM-03C-49,3S-T56B	ZB66K5E - (1) + ZB 76 K5E - (2)	49,25	21,43	1000 x 2800 x 2300	66	28	1	630	3	2,1	T5	23,53
CMC-CM-03C-51,9S-T56B	ZB76K5E - (3)	51,9	22,38	1000 x 2800 x 2300	66	28	1	630	3	2,1	T5	24,48
CMC-CM-04C-33,4S-T56B	ZB38KCE - (4)	33,36	15,48	1000 x 2450 x 1900	54	22	1	630	3	2,1	T5	17,58
CMC-CM-04C-39,1S-T56B	ZB45KCE - (4)	39,08	17,52	1000 x 2450 x 1900	54	22	1	630	3	2,1	T5	19,62
CMC-CM-04C-43,4S-T56B	ZB48KCE - (4)	43,4	19,48	1000 x 2800 x 2300	54	22	1	630	3	2,1	T5	21,58
CMC-CM-04C-50,0S-T56B	ZB57KCE - (4)	50	21,88	1000 x 2800 x 2300	66	28	1	630	3	2,1	T5	23,98
CMC-CM-04C-58,6S-T56B	ZB66K5E - (4)	58,6	26,04	1100 x 2800 x 2500	66	28	1	800	2	3,88	T5	29,92
CMC-CM-04C-69,2S-T56B	ZB76K5E - (4)	69,2	29,84	1100 x 3400 x 2500	66	28	1	800	3	5,82	T5	35,66
CMC-CM-05C-41,7S-T56B	ZB38KCE - (5)	41,7	19,35	1000 x 2800 x 2300	54	22	1	630	3	2,1	T5	21,45
CMC-CM-05C-48,9S-T56B	ZB45KCE - (5)	48,85	21,9	1000 x 2800 x 2300	54	22	1	630	3	2,1	T5	24
CMC-CM-05C-54,3S-T56B	ZB48KCE - (5)	54,25	24,35	1100 x 2800 x 2500	66	28	1	800	2	3,88	T5	28,23
CMC-CM-05C-62,5S-T56B	ZB57KCE - (5)	62,5	27,35	1100 x 2800 x 2500	66	28	1	800	2	3,88	T5	31,23
CMC-CM-05C-73,3S-T56B	ZB66K5E - (5)	73,25	32,55	1100 x 3400 x 2500	54	22	2	800	3	5,82	T5	38,37
CMC-CM-05C-86,5S-T56B	ZB76K5E - (5)	86,5	37,3	1100 x 3400 x 2500	66	28	2	800	3	5,82	T5	43,12

Capacity Values Specified In The Code : Evap. Temp. : -10 °C Condensing Temp. 45 °C . According To EN12900 Subcooling OK, Return Gas 20 °C

- Teknik bilgileri değiştirme hakkımız saklıdır. / We reserve the right to change technical informations.

KOMPAKT MERKEZİ SİSTEM - COMPACT CENTRAL SYSTEM

ÜRÜN KOD / PRODUCT CODE	MODEL - MİKTAR / MODEL - QUANTITY	R448A-R449A KAPASİTE / CAPACITY (Kilowatt) EN12900 (Subcooling OK, Return Gas 20 °C)								
		0°C			-5°C			-10°C		
		45	50	55	45	50	55	45	50	55
CMC-CM-02C-6,60S-T56B	ZB15KCE - (2)	9,94	9,16	8,28	8,16	7,48	6,72	6,6	6,02	5,38
CMC-CM-02C-7,66S-T56B	ZB19KCE - (2)	11,52	10,6	9,6	9,44	8,68	7,84	7,66	7,02	6,34
CMC-CM-02C-9,74S-T56B	ZB21KCE - (2)	14,44	13,42	12,34	11,92	11,06	10,16	9,74	9,04	8,28
CMC-CM-02C-11,1S-T56B	ZB26KCE - (2)	16,44	15,34	14,24	13,54	12,6	11,7	11,02	10,24	9,48
CMC-CM-02C-12,9S-T56B	ZB29KCE - (2)	18,96	17,76	16,52	15,66	14,68	13,66	12,86	12,04	11,22
CMC-CM-02C-16,7S-T56B	ZB38KCE - (2)	24,7	23	21,4	20,4	18,98	17,6	16,68	15,46	14,28
CMC-CM-02C-18,1S-T56B	ZB38KCE - (1) + ZB 45 KCE - (1)	26,8	25	23,25	22,15	20,59	19,1	18,11	16,79	15,51
CMC-CM-02C-19,5S-T56B	ZB45KCE - (2)	28,9	27	25,1	23,9	22,2	20,6	19,54	18,12	16,74
CMC-CM-02C-20,6S-T56B	ZB45KCE - (1) + ZB 48 KCE - (1)	31,05	29	26,95	25,65	23,85	22,15	20,97	19,46	17,98
CMC-CM-02C-21,7S-T56B	ZB48KCE - (2)	33,2	31	28,8	27,4	25,5	23,7	22,4	20,8	19,22
CMC-CM-03C-25,1S-T56B	ZB38KCE - (3)	37,05	34,5	32,1	30,6	28,47	26,4	25,02	23,19	21,42
CMC-CM-03C-26,5S-T56B	ZB38KCE - (2) + ZB 45 KCE - (1)	39,15	36,5	33,95	32,35	30,08	27,9	26,45	24,52	22,65
CMC-CM-03C-29,3S-T56B	ZB45KCE - (3)	43,35	40,5	37,65	35,85	33,3	30,9	29,31	27,18	25,11
CMC-CM-03C-30,4S-T56B	ZB45KCE - (2) + ZB 48 KCE - (1)	45,5	42,5	39,5	37,6	34,95	32,45	30,74	28,52	26,35
CMC-CM-03C-31,5S-T56B	ZB45KCE - (1) + ZB 48 KCE - (2)	47,65	44,5	41,35	39,35	36,6	34	32,17	29,86	27,59
CMC-CM-03C-32,6S-T56B	ZB48KCE - (3)	49,8	46,5	43,2	41,1	38,25	35,55	33,6	31,2	28,83
CMC-CM-03C-34,2S-T56B	ZB48KCE - (2) + ZB 57 KCE - (1)	52	48,6	45,2	42,85	39,95	37,1	35	32,5	30,02
CMC-CM-03C-37,5S-T56B	ZB57KCE - (3)	56,4	52,8	49,2	46,35	43,35	40,2	37,8	35,1	32,4
CMC-CM-03C-43,9S-T56B	ZB66K5E - (3)	65,7	61,2	56,25	54,15	50,1	45,9	43,95	40,5	36,75
CMC-CM-03C-46,6S-T56B	ZB66K5E - (2) + ZB 76 K5E - (1)	69,6	65	59,9	57,4	53,25	48,85	46,6	42,95	38,95
CMC-CM-03C-49,3S-T56B	ZB66K5E - (1) + ZB 76 K5E - (2)	73,5	68,8	63,55	60,65	56,4	51,8	49,25	45,4	41,15
CMC-CM-03C-51,9S-T56B	ZB76K5E - (3)	77,4	72,6	67,2	63,9	59,55	54,75	51,9	47,85	43,35
CMC-CM-04C-33,4S-T56B	ZB38KCE - (4)	49,4	46	42,8	40,8	37,96	35,2	33,36	30,92	28,56
CMC-CM-04C-39,1S-T56B	ZB45KCE - (4)	57,8	54	50,2	47,8	44,4	41,2	39,08	36,24	33,48
CMC-CM-04C-43,4S-T56B	ZB48KCE - (4)	66,4	62	57,6	54,8	51	47,4	44,8	41,6	38,44
CMC-CM-04C-50,0S-T56B	ZB57KCE - (4)	75,2	70,4	65,6	61,8	57,8	53,6	50,4	46,8	43,2
CMC-CM-04C-58,6S-T56B	ZB66K5E - (4)	87,6	81,6	75	72,2	66,8	61,2	58,6	54	49
CMC-CM-04C-69,2S-T56B	ZB76K5E - (4)	103,2	96,8	89,6	85,2	79,4	73	69,2	63,8	57,8
CMC-CM-05C-41,7S-T56B	ZB38KCE - (5)	61,75	57,5	53,5	51	47,45	44	41,7	38,65	35,7
CMC-CM-05C-48,9S-T56B	ZB45KCE - (5)	72,25	67,5	62,75	59,75	55,5	51,5	48,85	45,3	41,85
CMC-CM-05C-54,3S-T56B	ZB48KCE - (5)	83	77,5	72	68,5	63,75	59,25	56	52	48,05
CMC-CM-05C-62,5S-T56B	ZB57KCE - (5)	94	88	82	77,25	72,25	67	63	58,5	54
CMC-CM-05C-73,3S-T56B	ZB66K5E - (5)	109,5	102	93,75	90,25	83,5	76,5	73,25	67,5	61,25
CMC-CM-05C-86,5S-T56B	ZB76K5E - (5)	129	121	112	106,5	99,25	91,25	86,5	79,75	72,25

KOMPAKT MERKEZİ SİSTEM - COMPACT CENTRAL SYSTEM

ÜRÜN KOD / PRODUCT CODE	MODEL - MİKTAR / QUANTITY	KAPASİTE / CAPACITY KW	GÜÇ / POWER KW	GRUP ÖLÇÜLERİ / DIMENSIONS EN X BOY X YÜKS. / WIDTH X LENGTH X HEIGHT MM	BAĞLANTILAR / CONNECTIONS			FAN / FAN 900 RPM			ELEKTRİK / ELECTRICAL	
					EMİŞ / SUCT. MM	LİKİT / LIQUID MM	ADET / QTY.	ÇAP / DIA. MM	ADET / QTY.	GÜÇ / POWER KW	VOLTAJ / VOLTAGE	MAK. GÜÇ MAK. POWER KW
CMC-CM-02E-7,22S-T56B	SE6015GS-O - (2)	7,22	3,48	610 x 1400 x 1500	28	12	1	450	2	0,33	T5	3,81
CMC-CM-02E-8,62S-T56B	SE6018GS-O - (2)	8,62	3,94	610 x 1400 x 1500	28	12	1	450	2	0,33	T5	4,27
CMC-CM-02E-9,82S-T56B	SE6021GS-O - (2)	9,82	4,36	610 x 1400 x 1500	28	16	1	500	2	0,48	T5	4,84
CMC-CM-02E-12,4S-T56B	SE6026GS-O - (2)	12,4	5,5	610 x 1400 x 1500	35	16	1	500	2	0,48	T5	5,98
CMC-CM-02E-14,1S-T56B	SE6030GS-O - (2)	14,1	6,04	610 x 1400 x 1500	35	16	1	500	2	0,48	T5	6,52
CMC-CM-02E-17,2S-T56B	SE6036GS-O - (2)	17,2	7,28	600 x 1400 x 1700	35	16	1	500	2	0,48	T5	7,76
CMC-CM-02E-20,5S-T56B	SE6043GS-O - (2)	20,5	8,64	1000 x 1750 x 1900	42	16	1	630	2	1,4	T5	10,04
CMC-CM-02E-24,8S-T56B	SE6053GS-O - (2)	24,8	10,48	1000 x 1750 x 1900	42	16	1	630	2	1,4	T5	11,88
CMC-CM-03E-25,9S-T56B	SE6036GS-O - (3)	25,9	10,92	850 x 2150 x 1900	42	18	1	500	3	0,72	T5	11,64
CMC-CM-03E-27,5S-T56B	SE6036GS-O - (2) + SE6043GS-O - (1)	27,5	11,6	1000 x 2450 x 1900	54	22	1	630	3	2,1	T5	13,7
CMC-CM-03E-30,7S-T56B	SE6043GS-O - (3)	30,7	12,96	1000 x 2450 x 1900	54	22	1	630	3	2,1	T5	15,06
CMC-CM-03E-37,2S-T56B	SE6053GS-O - (3)	37,2	15,72	1000 x 2450 x 1900	54	22	1	630	3	2,1	T5	17,82
CMC-CM-03E-39,2S-T56B	SE6056GS-O - (3)	39,2	16,53	1000 x 2450 x 1900	54	22	1	630	3	2,1	T5	18,63
CMC-CM-03E-42,2S-T56B	SE6056GS-O - (2) + SE6067GS-O - (1)	42,2	17,8	1000 x 2800 x 2300	66	22	1	630	3	2,1	T5	19,9
CMC-CM-03E-45,2S-T56B	SE6056GS-O - (1) + SE6067GS-O - (2)	45,2	19,07	1000 x 2800 x 2300	66	28	1	630	3	2,1	T5	21,17
CMC-CM-03E-48,2S-T56B	SE6067GS-O - (3)	48,2	20,34	1000 x 2800 x 2300	66	28	1	630	3	2,1	T5	22,44
CMC-CM-03E-52,2S-T56B	SE6078GS-O - (2) + SE6067GS-O - (1)	52,2	22,06	1000 x 2800 x 2300	66	28	1	630	3	2,1	T5	24,16
CMC-CM-03E-54,3S-T56B	SE6078GS-O - (3)	54,3	22,92	1100 x 2800 x 2500	66	28	1	800	2	3,88	T5	26,8
CMC-CM-04E-34,5S-T56B	SE6036GS-O - (4)	34,5	14,56	1000 x 2450 x 1900	54	22	1	630	3	2,1	T5	16,66
CMC-CM-04E-40,9S-T56B	SE6043GS-O - (4)	40,9	17,28	1000 x 2450 x 1900	54	22	1	630	3	2,1	T5	19,38
CMC-CM-04E-49,6S-T56B	SE6053GS-O - (4)	49,6	20,96	1000 x 2800 x 2300	66	28	1	630	3	2,1	T5	23,06
CMC-CM-04E-52,3S-T56B	SE6056GS-O - (4)	52,3	22,04	1000 x 2800 x 2300	66	28	1	630	3	2,1	T5	24,14
CMC-CM-04E-64,3S-T56B	SE6067GS-O - (4)	64,3	27,12	1100 x 2800 x 2500	80	28	1	800	2	3,88	T5	31
CMC-CM-04E-72,4S-T56B	SE6078GS-O - (4)	72,4	30,56	1100 x 3400 x 2500	80	35	1	800	3	5,82	T5	36,38
CMC-CM-04E-79,2S-T56B	SE6085GS-O - (4)	79,2	33,08	1100 x 3400 x 2500	80	35	1	800	3	5,82	T5	38,9
CMC-CM-04E-83,4S-T56B	SE6089GS-O - (4)	83,4	34,8	1100 x 3400 x 2500	80	35	1	800	3	5,82	T5	40,62
CMC-CM-05E-43,1S-T56B	SE6036GS-O - (5)	43,1	18,2	1000 x 2800 x 2300	66	28	1	630	3	2,1	T5	20,3
CMC-CM-05E-51,2S-T56B	SE6043GS-O - (5)	51,2	21,6	1000 x 2800 x 2300	66	28	1	630	3	2,1	T5	23,7
CMC-CM-05E-62,1S-T56B	SE6053GS-O - (5)	62,1	26,2	1100 x 2800 x 2500	80	28	1	800	2	3,88	T5	30,08
CMC-CM-05E-65,4S-T56B	SE6056GS-O - (5)	65,4	27,55	1100 x 3400 x 2500	80	28	1	800	3	5,82	T5	33,37
CMC-CM-05E-80,4S-T56B	SE6067GS-O - (5)	80,4	33,9	1100 x 3400 x 2500	80	35	1	800	3	5,82	T5	39,72
CMC-CM-05E-90,6S-T56B	SE6078GS-O - (5)	90,6	38,2	1100 x 4400 x 2500	66	28	2	800	4	7,76	T5	45,96
CMC-CM-05E-99,1S-T56B	SE6085GS-O - (5)	99,1	41,35	1100 x 4400 x 2500	66	28	2	800	4	7,76	T5	49,11
CMC-CM-05E-0104S-T56B	SE6089GS-O - (5)	104,2	43,5	1100 x 4400 x 2500	66	28	2	800	4	7,76	T5	51,26

Capacity Values Specified In The Code : Evap. Temp. : -10 °C Condensing Temp. 45 °C . According To EN12900 Subcooling OK, Return Gas 20 °C

- Teknik bilgileri değiştirme hakkımız saklıdır. / We reserve the right to change technical informations.

KOMPAKT MERKEZİ SİSTEM - COMPACT CENTRAL SYSTEM

ÜRÜN KOD / PRODUCT CODE	MODEL - MİKTAR / MODEL - QUANTITY	R448A-R449A KAPASİTE / CAPACITY (Kilowatt) EN12900 (Subcooling OK, Return Gas 20 °C)								
		0°C			-5°C			-10°C		
		45	50	55	45	50	55	45	50	55
CMC-CM-02E-7,22S-T56B	SE6015GS-O - (2)	10,38	9,72	9,02	8,66	8,1	7,5	7,22	6,7	6,18
CMC-CM-02E-8,62S-T56B	SE6018GS-O - (2)	12,24	11,4	10,5	10,2	9,48	8,7	8,62	7,84	7,14
CMC-CM-02E-9,82S-T56B	SE6021GS-O - (2)	13,94	13	12	11,62	10,8	9,9	9,82	8,9	8,1
CMC-CM-02E-12,4S-T56B	SE6026GS-O - (2)	17,64	16,48	15,22	14,7	13,7	12,62	12,4	11,32	10,36
CMC-CM-02E-14,1S-T56B	SE6030GS-O - (2)	20,1	18,8	17,44	16,78	15,68	14,48	14,1	12,98	11,92
CMC-CM-02E-17,2S-T56B	SE6036GS-O - (2)	24,64	23,04	21,34	20,56	19,18	17,7	17,2	15,86	14,54
CMC-CM-02E-20,5S-T56B	SE6043GS-O - (2)	29,24	27,32	25,28	24,38	22,74	20,96	20,5	18,78	17,2
CMC-CM-02E-24,8S-T56B	SE6053GS-O - (2)	35,42	33,08	30,58	29,54	27,54	25,36	24,8	22,76	20,84
CMC-CM-03E-25,9S-T56B	SE6036GS-O - (3)	36,96	34,56	32,01	30,84	28,77	26,55	25,9	23,79	21,81
CMC-CM-03E-27,5S-T56B	SE6036GS-O - (2) + SE6043GS-O - (1)	39,26	36,7	33,98	32,75	30,55	28,18	27,5	25,25	23,14
CMC-CM-03E-30,7S-T56B	SE6043GS-O - (3)	43,86	40,98	37,92	36,57	34,11	31,44	30,7	28,17	25,8
CMC-CM-03E-37,2S-T56B	SE6053GS-O - (3)	53,13	49,62	45,87	44,31	41,31	38,04	37,2	34,14	31,26
CMC-CM-03E-39,2S-T56B	SE6056GS-O - (3)	56,01	52,32	48,42	46,68	43,56	40,14	39,2	36	32,94
CMC-CM-03E-42,2S-T56B	SE6056GS-O - (2) + SE6067GS-O - (1)	60,3	56,34	52,15	50,27	46,92	43,25	42,2	38,79	35,52
CMC-CM-03E-45,2S-T56B	SE6056GS-O - (1) + SE6067GS-O - (2)	64,59	60,36	55,88	53,86	50,28	46,36	45,2	41,58	38,1
CMC-CM-03E-48,2S-T56B	SE6067GS-O - (3)	68,88	64,38	59,61	57,45	53,64	49,47	48,2	44,37	40,38
CMC-CM-03E-52,2S-T56B	SE6078GS-O - (2) + SE6067GS-O - (1)	74,64	69,74	64,51	62,23	58,06	53,49	52,2	47,99	43,94
CMC-CM-03E-54,3S-T56B	SE6078GS-O - (3)	77,52	72,42	66,96	64,62	60,27	55,5	54,3	49,8	45,57
CMC-CM-04E-34,5S-T56B	SE6036GS-O - (4)	49,28	49,08	42,68	41,12	38,36	35,4	34,5	31,72	29,08
CMC-CM-04E-40,9S-T56B	SE6043GS-O - (4)	58,48	54,64	50,56	48,76	45,48	41,92	40,9	37,56	34,4
CMC-CM-04E-49,6S-T56B	SE6053GS-O - (4)	70,84	66,16	61,16	59,08	55,08	50,72	49,6	45,52	41,68
CMC-CM-04E-52,3S-T56B	SE6056GS-O - (4)	74,68	69,76	64,56	62,24	58,08	53,52	52,3	48	43,92
CMC-CM-04E-64,3S-T56B	SE6067GS-O - (4)	91,84	85,84	79,48	76,6	71,52	65,96	64,3	59,16	54,24
CMC-CM-04E-72,4S-T56B	SE6078GS-O - (4)	103,36	96,56	89,28	86,16	80,36	74	72,4	66,4	60,76
CMC-CM-04E-79,2S-T56B	SE6085GS-O - (4)	113,08	105,64	97,68	94,28	87,92	81	79,2	72,64	66,48
CMC-CM-04E-83,4S-T56B	SE6089GS-O - (4)	118,84	111	102,6	99,08	92,36	85	83,4	76,28	69,76
CMC-CM-05E-43,1S-T56B	SE6036GS-O - (5)	61,6	57,6	53,35	51,4	47,95	44,25	43,1	39,65	36,35
CMC-CM-05E-51,2S-T56B	SE6043GS-O - (5)	73,1	68,3	63,2	60,95	56,85	52,4	51,2	46,95	43
CMC-CM-05E-62,1S-T56B	SE6053GS-O - (5)	88,55	82,7	76,45	73,85	68,85	63,4	62,1	56,9	52,1
CMC-CM-05E-65,4S-T56B	SE6056GS-O - (5)	93,35	87,2	80,7	77,8	72,6	66,9	65,4	60	54,9
CMC-CM-05E-80,4S-T56B	SE6067GS-O - (5)	114,8	107,3	99,35	95,75	89,4	82,45	80,4	73,95	67,8
CMC-CM-05E-90,6S-T56B	SE6078GS-O - (5)	129,2	120,7	111,6	107,7	100,45	92,5	90,6	83	75,95
CMC-CM-05E-99,1S-T56B	SE6085GS-O - (5)	141,35	132,05	122,1	117,85	109,9	101,25	99,1	90,8	83,1
CMC-CM-05E-0104S-T56B	SE6089GS-O - (5)	148,55	138,75	128,25	123,85	115,45	106,25	104,2	95,35	87,2

KOMPAKT MERKEZİ SİSTEM - COMPACT CENTRAL SYSTEM

ÜRÜN KOD / PRODUCT CODE	MODEL - MİKTAR / QUANTITY	KAPASİTE / CAPACITY	GÜÇ / POWER KW	GRUP ÖLÇÜLERİ / DIMENSIONS EN X BOY X YÜKS. / WIDTH X LENGTH X HEIGHT MM	BAĞLANTILAR / CONNECTIONS			FAN / FAN 900 RPM			ELEKTRİK / ELECTRICAL	
					EMİS / SUCT. MM	LİKİT / LIQUID MM	ADET / QTY.	ÇAP / DIA. MM	ADET / QTY.	GÜÇ / POWER KW	VOLTAJ / VOLTAGE	MAK. GÜÇ MAK. POWER KW
CMC-SL-02B-2,44S-T56B	2EES-2(Y) - (2)	2,44	1,98	850 x 1550 x 1900	28	12	1	450	2	0,33	T5	2,31
CMC-SL-02B-2,96S-T56B	2DES-2(Y) - (2)	2,96	2,42	850 x 1550 x 1900	35	16	1	450	2	0,33	T5	2,75
CMC-SL-02B-4,02S-T56B	2CES-3(Y) - (2)	4,02	3,28	850 x 1550 x 1900	35	16	1	450	2	0,33	T5	3,61
CMC-SL-02B-4,32S-T56B	4FES-3(Y) - (2)	4,32	3,54	850 x 1550 x 1900	35	16	1	450	2	0,33	T5	3,87
CMC-SL-02B-5,34S-T56B	4EES-4(Y) - (2)	5,34	4,26	850 x 1550 x 1900	42	16	1	500	2	0,48	T5	4,74
CMC-SL-02B-6,02S-T56B	4DES-5(Y) - (2)	6,02	4,82	850 x 1550 x 1900	42	18	1	450	2	0,33	T5	5,15
CMC-SL-02B-8,12S-T56B	4CES-6(Y) - (2)	8,12	6,48	1000 x 1750 x 1900	54	22	1	630	2	1,4	T5	7,88
CMC-SL-03B-6,48S-T56B	4FES-3(Y) - (3)	6,48	5,31	850 x 2150 x 1900	42	18	1	500	3	0,72	T5	6,03
CMC-SL-03B-8,01S-T56B	4EES-4(Y) - (3)	8,01	6,39	850 x 2150 x 1900	54	22	1	500	3	0,72	T5	7,11
CMC-SL-03B-9,03S-T56B	4DES-5(Y) - (3)	9,03	7,23	850 x 2150 x 1900	54	22	1	500	3	0,72	T5	7,95
CMC-SL-03B-10,1S-T56B	4DES-5(Y) - (2) + 4CES-6(Y) - (1)	10,1	8,06	850 x 2150 x 1900	54	22	1	500	3	0,72	T5	8,78
CMC-SL-03B-12,2S-T56B	4CES-6(Y) - (3)	12,2	9,72	850 x 2150 x 1900	54	22	1	500	3	0,72	T5	10,44
CMC-SL-03B-12,9S-T56B	4VES-7(Y) - (1) + 4TES-9(Y) - (2)	12,9	9,69	1000 x 2450 x 1900	66	28	1	630	3	2,1	T5	11,79
CMC-SL-03B-14,1S-T56B	4TES-9(Y) - (3)	14,1	10,47	1000 x 2450 x 1900	66	28	1	630	3	2,1	T5	12,57
CMC-SL-03B-14,6S-T56B	4PES-12(Y) - (3)	14,6	10,62	1000 x 2450 x 1900	66	28	1	630	3	2,1	T5	12,72
CMC-SL-03B-16,1S-T56B	4PES-12(Y) - (2) + 4NES-14(Y) - (1)	16,1	11,64	1000 x 2450 x 1900	66	28	1	630	3	2,1	T5	13,74
CMC-SL-03B-17,6S-T56B	4PES-12(Y) - (1) + 4NES-14(Y) - (2)	17,6	12,66	1000 x 2450 x 1900	66	28	1	630	3	2,1	T5	14,76
CMC-SL-03B-19,1S-T56B	4NES-14(Y) - (3)	19,1	13,68	1000 x 2800 x 2300	66	28	1	630	3	2,1	T5	15,78
CMC-SL-04B-19,4S-T56B	4PES-12(Y) - (4)	19,4	14,16	1000 x 2800 x 2300	54	22	2	630	3	2,1	T5	16,26
CMC-SL-04B-20,9S-T56B	4PES-12(Y) - (3) + 4NES-14(Y) - (1)	20,9	15,18	1000 x 2800 x 2300	54	22	2	630	3	2,1	T5	17,28
CMC-SL-04B-22,4S-T56B	4PES-12(Y) - (2) + 4NES-14(Y) - (2)	22,4	16,2	1000 x 2800 x 2300	54	22	2	630	3	2,1	T5	18,3
CMC-SL-04B-23,9S-T56B	4PES-12(Y) - (1) + 4NES-14(Y) - (3)	23,9	17,22	1100 x 2800 x 2500	54	22	2	800	2	3,88	T5	21,1
CMC-SL-04B-25,4S-T56B	4NES-14(Y) - (4)	25,4	18,24	1100 x 2800 x 2500	54	22	2	800	2	3,88	T5	22,12
CMC-SL-04B-31,2S-T56B	4JE-15(Y) - (4)	31,2	23,12	1100 x 3400 x 2500	66	28	2	800	3	5,82	T5	28,94
CMC-SL-04B-33,1S-T56B	4JE-15(Y) - (3) + 4HE-18(Y) - (1)	33,1	24,6	1100 x 3400 x 2500	66	28	2	800	3	5,82	T5	30,42
CMC-SL-04B-34,9S-T56B	4JE-15(Y) - (2) + 4HE-18(Y) - (2)	34,9	26,08	1100 x 3400 x 2500	80	35	2	800	3	5,82	T5	31,9
CMC-SL-04B-36,7S-T56B	4JE-15(Y) - (1) + 4HE-18(Y) - (3)	36,7	27,56	1100 x 3400 x 2500	80	35	2	800	3	5,82	T5	33,38
CMC-SL-04B-38,6S-T56B	4HE-18(Y) - (4)	38,6	29,04	1100 x 3400 x 2500	80	35	2	800	3	5,82	T5	34,86
CMC-SL-04B-40,8S-T56B	4HE-18(Y) - (3) + 4GE-23(Y) - (1)	40,8	30,64	1100 x 3400 x 2500	80	35	2	800	3	5,82	T5	36,46
CMC-SL-04B-42,9S-T56B	4HE-18(Y) - (2) + 4GE-23(Y) - (2)	42,9	32,24	1100 x 4400 x 2500	80	35	2	800	4	7,76	T5	40

Capacity Values Specified In The Code : Evap. Temp. : -35 °C Condensing Temp. 45 °C . According To EN12900 Subcooling OK, Return Gas 20 °C

- Teknik bilgileri değiştirme hakkımız saklıdır. / We reserve the right to change technical informations.

KOMPAKT MERKEZİ SİSTEM - COMPACT CENTRAL SYSTEM

ÜRÜN KOD / PRODUCT CODE	MODEL - MİKTAR / MODEL - QUANTITY	R448A-R449A KAPASİTE / CAPACITY (Kilowatt) EN12900 (Subcooling OK, Return Gas 20 °C)								
		-25°C			-30°C			-35°C		
		45	50	55	45	50	55	45	50	55
CMC-SL-02B-2,44S-T56B	2EES-2(Y) - (2)	4,9	4,34	3,8	3,54	3,1	2,64	2,44	2,08	N/A
CMC-SL-02B-2,96S-T56B	2DES-2(Y) - (2)	5,78	5,16	4,54	4,24	3,72	3,24	2,96	2,56	N/A
CMC-SL-02B-4,02S-T56B	2CES-3(Y) - (2)	7,54	6,8	6,06	5,62	5	4,4	4,02	3,54	N/A
CMC-SL-02B-4,32S-T56B	4FES-3(Y) - (2)	8,18	7,34	6,52	6,06	5,38	4,72	4,32	3,78	N/A
CMC-SL-02B-5,34S-T56B	4EES-4(Y) - (2)	10,2	9,14	8,1	7,52	6,68	5,84	5,34	4,68	N/A
CMC-SL-02B-6,02S-T56B	4DES-5(Y) - (2)	11,56	10,34	9,16	8,5	7,54	6,58	6,02	5,24	N/A
CMC-SL-02B-8,12S-T56B	4CES-6(Y) - (2)	15,1	13,62	12,16	11,26	10,08	8,92	8,12	7,2	N/A
CMC-SL-03B-6,48S-T56B	4FES-3(Y) - (3)	12,27	11,01	9,78	9,09	8,07	7,08	6,48	5,67	N/A
CMC-SL-03B-8,01S-T56B	4EES-4(Y) - (3)	15,3	13,71	12,15	11,28	10,02	8,76	8,01	7,02	N/A
CMC-SL-03B-9,03S-T56B	4DES-5(Y) - (3)	17,34	15,51	13,74	12,75	11,31	9,87	9,03	7,86	N/A
CMC-SL-03B-10,1S-T56B	4DES-5(Y) - (2) + 4CES-6(Y) - (1)	19,11	17,15	15,24	14,13	12,58	11,04	10,08	8,84	N/A
CMC-SL-03B-12,2S-T56B	4CES-6(Y) - (3)	22,65	20,43	18,24	16,89	15,12	13,38	12,18	10,8	N/A
CMC-SL-03B-12,9S-T56B	4VES-7(Y) - (1) + 4TES-9(Y) - (2)	25,56	22,73	19,94	18,61	16,33	12,02	12,97	9,45	7,35
CMC-SL-03B-14,1S-T56B	4TES-9(Y) - (3)	27,42	24,45	21,51	20,07	17,67	12,96	14,1	10,23	7,98
CMC-SL-03B-14,6S-T56B	4PES-12(Y) - (3)	29,88	26,22	22,62	21,42	18,42	13,68	14,55	10,74	8,19
CMC-SL-03B-16,1S-T56B	4PES-12(Y) - (2) + 4NES-14(Y) - (1)	32,32	28,46	24,65	23,35	20,19	14,95	16,06	11,78	9,05
CMC-SL-03B-17,6S-T56B	4PES-12(Y) - (1) + 4NES-14(Y) - (2)	34,76	30,7	26,68	25,28	21,96	16,22	17,57	12,82	9,91
CMC-SL-03B-19,1S-T56B	4NES-14(Y) - (3)	37,2	32,94	28,71	27,21	23,73	17,49	19,08	13,86	10,77
CMC-SL-04B-19,4S-T56B	4PES-12(Y) - (4)	39,84	34,96	30,16	28,56	24,56	18,24	19,4	14,32	10,92
CMC-SL-04B-20,9S-T56B	4PES-12(Y) - (3) + 4NES-14(Y) - (1)	42,28	37,2	32,19	30,49	26,33	19,51	20,91	15,36	11,78
CMC-SL-04B-22,4S-T56B	4PES-12(Y) - (2) + 4NES-14(Y) - (2)	44,72	39,44	34,22	32,42	28,1	20,78	22,42	16,4	12,64
CMC-SL-04B-23,9S-T56B	4PES-12(Y) - (1) + 4NES-14(Y) - (3)	47,16	41,68	36,25	34,35	29,87	22,05	23,93	17,44	13,5
CMC-SL-04B-25,4S-T56B	4NES-14(Y) - (4)	49,6	43,92	38,28	36,28	31,64	23,32	25,44	18,48	14,36
CMC-SL-04B-31,2S-T56B	4JE-15(Y) - (4)	59,72	54,48	47,44	44,12	39,04	28,96	31,16	22,88	18,2
CMC-SL-04B-33,1S-T56B	4JE-15(Y) - (3) + 4HE-18(Y) - (1)	62,67	42	50	46,47	41,25	30,52	33,02	24,17	19,29
CMC-SL-04B-34,9S-T56B	4JE-15(Y) - (2) + 4HE-18(Y) - (2)	65,62	49,52	52,56	48,82	43,46	32,08	34,88	25,46	20,38
CMC-SL-04B-36,7S-T56B	4JE-15(Y) - (1) + 4HE-18(Y) - (3)	68,57	57,04	55,12	51,17	45,67	33,64	36,74	26,75	21,47
CMC-SL-04B-38,6S-T56B	4HE-18(Y) - (4)	71,52	64,56	57,68	53,52	47,88	35,2	38,6	28,04	22,56
CMC-SL-04B-40,8S-T56B	4HE-18(Y) - (3) + 4GE-23(Y) - (1)	74,84	67,71	60,64	56,23	50,47	37	40,79	29,54	23,86
CMC-SL-04B-42,9S-T56B	4HE-18(Y) - (2) + 4GE-23(Y) - (2)	78,16	70,86	63,6	58,94	53,06	38,8	42,98	31,04	25,16

KOMPAKT MERKEZİ SİSTEM - COMPACT CENTRAL SYSTEM

ÜRÜN KOD / PRODUCT CODE	MODEL - MİKTAR / QUANTITY	KAPASİTE / CAPACITY	GÜÇ / POWER KW	GRUP ÖLÇÜLERİ / DIMENSIONS EN X BOY X YÜKS. / WIDTH X LENGTH X HEIGHT MM	BAĞLANTILAR / CONNECTIONS			FAN / FAN 900 RPM			ELEKTRİK / ELECTRICAL	
					EMİŞ / SUCT. MM	LİKİT / LIQUID MM	ADET / QTY.	ÇAP / DIA. MM	ADET / QTY.	GÜÇ / POWER KW	VOLTAJ / VOLTAGE	MAK. GÜÇ MAX. POWER KW
CMC-SL-02D-2,38S-T56B	H 201 CS - (2)	2,38	2,28	850 x 1550 x 1900	28	12	1	450	2	0,33	T5	2,61
CMC-SL-02D-2,84S-T56B	H 251 CS - (2)	2,84	2,82	850 x 1550 x 1900	28	12	1	450	2	0,33	T5	3,15
CMC-SL-02D-3,66S-T56B	H 290 CS - (2)	3,66	2,94	850 x 1550 x 1900	35	16	1	450	2	0,33	T5	3,27
CMC-SL-02D-4,20S-T56B	H 300 CS - (2)	4,2	3,28	850 x 1550 x 1900	35	16	1	450	2	0,33	T5	3,61
CMC-SL-02D-5,48S-T56B	H 390 CS - (2)	5,48	4,66	850 x 1550 x 1900	35	16	1	450	2	0,33	T5	4,99
CMC-SL-02D-5,82S-T56B	H 405 CS - (2)	5,82	4,58	850 x 1550 x 1900	42	18	1	500	2	0,48	T5	5,06
CMC-SL-02D-6,72S-T56B	H 505 CS - (2)	6,72	5,28	850 x 1550 x 1900	42	18	1	500	2	0,48	T5	5,76
CMC-SL-02D-7,90S-T56B	H 705 CS - (2)	7,9	6,12	850 x 1550 x 1900	42	18	1	500	2	0,48	T5	6,6
CMC-SL-03D-6,30S-T56B	H 300 CS - (3)	6,3	4,92	850 x 2150 x 1900	42	18	1	500	3	0,72	T5	5,64
CMC-SL-03D-8,22S-T56B	H 390 CS - (3)	8,22	6,99	850 x 2150 x 1900	42	18	1	500	3	0,72	T5	7,71
CMC-SL-03D-8,73S-T56B	H 405 CS - (3)	8,73	6,87	850 x 2150 x 1900	54	22	1	500	3	0,72	T5	7,59
CMC-SL-03D-10,1S-T56B	H 505 CS - (3)	10,1	7,92	850 x 2150 x 1900	54	22	1	500	3	0,72	T5	8,64
CMC-SL-03D-10,7S-T56B	H 505 CS - (2) + H 705 CS - (1)	10,7	8,34	850 x 2150 x 1900	54	22	1	500	3	0,72	T5	9,06
CMC-SL-03D-11,9S-T56B	H 705 CS - (3)	11,9	9,18	850 x 2150 x 1900	54	22	1	500	3	0,72	T5	9,9
CMC-SL-03D-13,7S-T56B	H 751 CS - (3)	13,7	10,83	1000 x 2450 x 1900	66	28	1	630	3	2,1	T5	12,93
CMC-SL-03D-14,5S-T56B	H 751 CS - (2) + H 801 CS - (1)	14,5	11,47	1000 x 2450 x 1900	66	28	1	630	3	2,1	T5	13,57
CMC-SL-03D-15,4S-T56B	H 751 CS - (1) + H 801 CS - (2)	15,4	12,11	1000 x 2450 x 1900	66	28	1	630	3	2,1	T5	14,21
CMC-SL-03D-16,2S-T56B	H 801 CS - (3)	16,2	12,75	1000 x 2450 x 1900	66	28	1	630	3	2,1	T5	14,85
CMC-SL-03D-17,6S-T56B	H 901 CS - (3)	17,6	13,95	1000 x 2450 x 1900	66	28	1	630	3	2,1	T5	16,05
CMC-SL-03D-19,5S-T56B	H 1001 CS - (3)	19,5	13,95	1000 x 2450 x 1900	66	28	1	630	3	2,1	T5	16,05
CMC-SL-04D-21,6S-T56B	H 801 CS - (4)	21,6	17	1100 x 2800 x 2500	54	22	2	800	2	3,88	T5	20,88
CMC-SL-04D-23,5S-T56B	H 901 CS - (4)	23,5	18,6	1000 x 2800 x 2300	54	22	2	630	3	2,1	T5	20,7
CMC-SL-04D-26,1S-T56B	H 1001 CS - (4)	26,1	18,6	1000 x 2800 x 2300	54	22	2	630	3	2,1	T5	20,7
CMC-SL-04D-27,1S-T56B	H 1001 CS - (3) + H 1501 CS - (1)	27,1	19,54	1100 x 2800 x 2500	66	28	2	800	2	3,88	T5	23,42
CMC-SL-04D-28,1S-T56B	H 1001 CS - (2) + H 1501 CS - (2)	28,1	20,48	1100 x 2800 x 2500	66	28	2	800	2	3,88	T5	24,36
CMC-SL-04D-29,2S-T56B	H 1001 CS - (1) + H 1501 CS - (3)	29,2	21,42	1000 x 3200 x 2300	66	28	2	630	4	2,8	T5	24,22
CMC-SL-04D-30,2S-T56B	H 1501 CS - (4)	30,2	22,36	1100 x 2800 x 2500	66	28	2	800	2	3,88	T5	26,24
CMC-SL-04D-31,9S-T56B	H 1501 CS - (2) + H 1601 CS - (2)	31,9	24,08	1000 x 3200 x 2300	66	28	2	630	4	2,8	T5	26,88
CMC-SL-04D-33,5S-T56B	H 1601 CS - (4)	33,5	25,8	1100 x 3400 x 2500	66	28	2	800	3	5,82	T5	31,62
CMC-SL-04D-37,5S-T56B	H 2000 CS - (4)	37,5	30,6	1100 x 3400 x 2500	80	35	2	800	3	5,82	T5	36,42
CMC-SL-04D-38,5S-T56B	H 2000 CS - (3) + H 2500 CS - (1)	38,5	32,03	1100 x 3400 x 2500	80	35	2	800	3	5,82	T5	37,85
CMC-SL-04D-39,4S-T56B	H 2000 CS - (2) + H 2500 CS - (2)	39,4	33,46	1100 x 3400 x 2500	80	35	2	800	3	5,82	T5	39,28

Capacity Values Specified In The Code : Evap. Temp. : -35 °C Condensing Temp. 45 °C . According To EN12900 Subcooling OK, Return Gas 20 °C

- Teknik bilgileri değiştirme hakkımız saklıdır. / We reserve the right to change technical informations.

KOMPAKT MERKEZİ SİSTEM - COMPACT CENTRAL SYSTEM

ÜRÜN KOD / PRODUCT CODE	MODEL - MİKTAR / MODEL - QUANTITY	R448A-R449A KAPASİTE / CAPACITY (Kilowatt) EN12900 (Subcooling OK, Return Gas 20 °C)								
		-25°C			-30°C			-35°C		
		45	50	55	45	50	55	45	50	55
CMC-SL-02D-2,38S-T56B	H 201 CS - (2)	4,36	3,92	3,52	3,28	2,94	N/A	2,38	N/A	N/A
CMC-SL-02D-2,84S-T56B	H 251 CS - (2)	5,28	4,78	4,3	3,94	3,54	N/A	2,84	N/A	N/A
CMC-SL-02D-3,66S-T56B	H 290 CS - (2)	6,8	6,08	5,38	5,08	4,5	N/A	3,66	N/A	N/A
CMC-SL-02D-4,20S-T56B	H 300 CS - (2)	7,6	6,84	6,1	5,74	5,12	N/A	4,2	N/A	N/A
CMC-SL-02D-5,48S-T56B	H 390 CS - (2)	9,4	8,62	7,86	7,26	6,64	N/A	5,48	N/A	N/A
CMC-SL-02D-5,82S-T56B	H 405 CS - (2)	10,72	9,72	8,74	8,04	7,24	N/A	5,82	N/A	N/A
CMC-SL-02D-6,72S-T56B	H 505 CS - (2)	12,4	11,3	10,24	9,3	8,44	N/A	6,72	N/A	N/A
CMC-SL-02D-7,90S-T56B	H 705 CS - (2)	14,62	13,34	12,08	10,94	9,92	N/A	7,9	N/A	N/A
CMC-SL-03D-6,30S-T56B	H 300 CS - (3)	11,4	10,26	9,15	8,61	7,68	N/A	6,3	N/A	N/A
CMC-SL-03D-8,22S-T56B	H 390 CS - (3)	14,1	12,93	11,79	10,89	9,96	N/A	8,22	N/A	N/A
CMC-SL-03D-8,73S-T56B	H 405 CS - (3)	16,08	14,58	13,11	12,06	10,86	N/A	8,73	N/A	N/A
CMC-SL-03D-10,1S-T56B	H 505 CS - (3)	18,6	16,95	15,36	13,95	12,66	N/A	10,08	N/A	N/A
CMC-SL-03D-10,7S-T56B	H 505 CS - (2) + H 705 CS - (1)	19,71	17,97	16,28	14,77	13,4	N/A	10,67	N/A	N/A
CMC-SL-03D-11,9S-T56B	H 705 CS - (3)	21,93	20,01	18,12	16,41	14,88	N/A	11,85	N/A	N/A
CMC-SL-03D-13,7S-T56B	H 751 CS - (3)	25,14	22,8	20,61	18,87	17,04	N/A	13,68	N/A	N/A
CMC-SL-03D-14,5S-T56B	H 751 CS - (2) + H 801 CS - (1)	26,77	24,3	21,96	20,08	18,14	N/A	14,53	N/A	N/A
CMC-SL-03D-15,4S-T56B	H 751 CS - (1) + H 801 CS - (2)	28,4	25,8	23,31	21,29	19,24	N/A	15,38	N/A	N/A
CMC-SL-03D-16,2S-T56B	H 801 CS - (3)	30,03	27,3	24,66	22,5	20,34	N/A	16,23	N/A	N/A
CMC-SL-03D-17,6S-T56B	H 901 CS - (3)	32,76	29,73	26,85	24,48	22,11	N/A	17,64	N/A	N/A
CMC-SL-03D-19,5S-T56B	H 1001 CS - (3)	35,43	31,95	28,47	26,73	23,88	N/A	19,53	N/A	N/A
CMC-SL-04D-21,6S-T56B	H 801 CS - (4)	40,04	36,4	32,88	30	27,12	N/A	21,64	N/A	N/A
CMC-SL-04D-23,5S-T56B	H 901 CS - (4)	43,68	39,64	35,8	32,64	29,48	N/A	23,52	N/A	N/A
CMC-SL-04D-26,1S-T56B	H 1001 CS - (4)	47,24	42,6	37,96	35,64	31,84	N/A	26,04	N/A	N/A
CMC-SL-04D-27,1S-T56B	H 1001 CS - (3) + H 1501 CS - (1)	49,21	44,36	39,52	37,11	33,13	N/A	27,09	N/A	N/A
CMC-SL-04D-28,1S-T56B	H 1001 CS - (2) + H 1501 CS - (2)	51,18	46,12	41,08	38,58	34,42	N/A	28,14	N/A	N/A
CMC-SL-04D-29,2S-T56B	H 1001 CS - (1) + H 1501 CS - (3)	53,15	47,88	42,64	40,05	35,71	N/A	29,19	N/A	N/A
CMC-SL-04D-30,2S-T56B	H 1501 CS - (4)	55,12	49,64	44,2	41,52	37	N/A	30,24	N/A	N/A
CMC-SL-04D-31,9S-T56B	H 1501 CS - (2) + H 1601 CS - (2)	58,22	52,62	47,12	43,8	39,26	N/A	31,86	N/A	N/A
CMC-SL-04D-33,5S-T56B	H 1601 CS - (4)	61,32	55,6	50,04	46,08	41,52	N/A	33,48	N/A	N/A
CMC-SL-04D-37,5S-T56B	H 2000 CS - (4)	71,8	64,84	57,96	53,12	47,4	N/A	37,52	N/A	N/A
CMC-SL-04D-38,5S-T56B	H 2000 CS - (3) + H 2500 CS - (1)	73,78	66,62	59,55	54,53	48,66	N/A	38,48	N/A	N/A
CMC-SL-04D-39,4S-T56B	H 2000 CS - (2) + H 2500 CS - (2)	75,76	68,4	61,14	55,94	49,92	N/A	39,44	N/A	N/A

KOMPAKT MERKEZİ SİSTEM - COMPACT CENTRAL SYSTEM

ÜRÜN KOD / PRODUCT CODE	MODEL - MİKTAR / QUANTITY	KAPASİTE / CAPACITY	GÜÇ / POWER KW	GRUP ÖLÇÜLERİ / DIMENSIONS EN X BOY X YÜKS. / WIDTH X LENGTH X HEIGHT MM	BAĞLANTILAR / CONNECTIONS			FAN / FAN 900 RPM			ELEKTRİK / ELECTRICAL	
					EMİŞ / SUCT. MM	LİKİT / LIQUID MM	ADET / QTY.	ÇAP / DIA. MM	ADET / QTY.	GÜÇ / POWER KW	VOLTAJ / VOLTAGE	MAK. GÜÇ / MAX. POWER KW
CMC-SL-02F-1,70S-T56B	B1.5-10.IY - (2)	1,7	1,78	850 x 1550 x 1900	28	12	1	450	2	0,33	T5	2,11
CMC-SL-02F-3,02S-T56B	D2-13.IY - (2)	3,02	2,44	850 x 1550 x 1900	35	16	1	450	2	0,33	T5	2,77
CMC-SL-02F-3,52S-T56B	D2-15.IY - (2)	3,52	2,9	850 x 1550 x 1900	35	16	1	450	2	0,33	T5	3,23
CMC-SL-02F-4,78S-T56B	D4-19.IY - (2)	4,78	3,9	850 x 1550 x 1900	35	16	1	450	2	0,33	T5	4,23
CMC-SL-02F-5,88S-T56B	Q4-25.IY - (2)	5,88	4,78	850 x 1550 x 1900	42	18	1	500	2	0,48	T5	5,26
CMC-SL-02F-6,12S-T56B	Q5-28.IY - (2)	6,12	5,4	850 x 1550 x 1900	42	18	1	500	2	0,48	T5	5,88
CMC-SL-02F-7,12S-T56B	Q5-33.IY - (2)	7,12	6,3	850 x 1550 x 1900	54	22	1	500	2	0,48	T5	6,78
CMC-SL-03F-6,15S-T56B	D3-16.IY - (3)	6,15	4,95	850 x 2150 x 1900	42	18	1	500	3	0,72	T5	5,67
CMC-SL-03F-7,83S-T56B	Q4-21.IY - (3)	7,83	6,12	850 x 2150 x 1900	42	18	1	500	3	0,72	T5	6,84
CMC-SL-03F-8,82S-T56B	Q4-25.IY - (3)	8,82	7,17	850 x 2150 x 1900	54	22	1	500	3	0,72	T5	7,89
CMC-SL-03F-8,94S-T56B	Q4-25.IY - (2) + Q5-28.IY - (1)	8,94	7,48	850 x 2150 x 1900	54	22	1	500	3	0,72	T5	8,2
CMC-SL-03F-9,18S-T56B	Q5-28.IY - (3)	9,18	8,1	850 x 2150 x 1900	54	22	1	500	3	0,72	T5	8,82
CMC-SL-03F-9,68S-T56B	Q5-28.IY - (2) + Q5-33.IY - (1)	9,68	8,55	850 x 2150 x 1900	54	22	1	500	3	0,72	T5	9,27
CMC-SL-03F-10,7S-T56B	Q5-33.IY - (3)	10,7	9,45	850 x 2150 x 1900	54	22	1	500	3	0,72	T5	10,17
CMC-SL-03F-13,5S-T56B	Q7-36.IY - (3)	13,5	10,74	1000 x 2450 x 1900	66	28	1	630	3	2,1	T5	12,84
CMC-SL-03F-14,1S-T56B	S8-42Y - (3)	14,1	10,41	1000 x 2450 x 1900	66	28	1	630	3	2,1	T5	12,51
CMC-SL-03F-14,5S-T56B	S8-42Y - (2) + S10-52Y - (1)	14,5	10,67	1000 x 2450 x 1900	66	28	1	630	3	2,1	T5	12,77
CMC-SL-03F-14,9S-T56B	S8-42Y - (1) + S10-52Y - (2)	14,9	10,93	1000 x 2450 x 1900	66	28	1	630	3	2,1	T5	13,03
CMC-SL-03F-15,4S-T56B	S10-52Y - (3)	15,4	11,19	1000 x 2450 x 1900	66	35	1	630	3	2,1	T5	13,29
CMC-SL-04F-19,2S-T56B	S8-42Y - (3) + S10-52Y - (1)	19,2	14,14	1000 x 3200 x 2300	54	22	2	630	4	2,8	T5	16,94
CMC-SL-04F-19,7S-T56B	S8-42Y - (2) + S10-52Y - (2)	19,7	14,4	1000 x 3200 x 2300	54	22	2	630	4	2,8	T5	17,2
CMC-SL-04F-20,1S-T56B	S8-42Y - (1) + S10-52Y - (3)	20,1	14,66	1000 x 3200 x 2300	54	22	2	630	4	2,8	T5	17,46
CMC-SL-04F-20,6S-T56B	S10-52Y - (4)	20,6	14,92	1000 x 3200 x 2300	66	28	2	630	4	2,8	T5	17,72
CMC-SL-04F-22,9S-T56B	S10-52Y - (2) + S15-56Y - (2)	22,9	16,56	1000 x 3200 x 2300	66	28	2	630	4	2,8	T5	19,36
CMC-SL-04F-25,2S-T56B	S15-56Y - (4)	25,2	18,2	1000 x 3200 x 2300	66	28	2	630	4	2,8	T5	21
CMC-SL-04F-29,1S-T56B	V15-59Y - (4)	29,1	21,56	1000 x 3200 x 2300	66	28	2	630	4	2,8	T5	24,36
CMC-SL-04F-31,0S-T56B	V15-59Y - (3) + V15-71Y - (1)	31	23,14	1100 x 3400 x 2500	66	28	2	800	3	5,82	T5	28,96
CMC-SL-04F-33,0S-T56B	V15-59Y - (2) + V15-71Y - (2)	33	24,72	1100 x 3400 x 2500	66	28	2	800	3	5,82	T5	30,54
CMC-SL-04F-35,0S-T56B	V15-59Y - (1) + V15-71Y - (3)	35	26,3	1100 x 3400 x 2500	80	35	2	800	3	5,82	T5	32,12
CMC-SL-04F-37,0S-T56B	V15-71Y - (4)	37	27,88	1100 x 3400 x 2500	80	35	2	800	3	5,82	T5	33,7
CMC-SL-04F-42,0S-T56B	V15-71Y - (2) + V20-84Y - (2)	42	31,22	1100 x 3400 x 2500	80	35	2	800	3	5,82	T5	37,04
CMC-SL-04F-47,1S-T56B	V20-84Y - (4)	47,1	34,56	1100 x 4400 x 2500	80	35	2	800	4	7,76	T5	42,32

Capacity Values Specified In The Code : Evap. Temp. : -35 °C Condensing Temp. 45 °C . According To EN12900 Subcooling OK, Return Gas 20 °C

- Teknik bilgileri değiştirme hakkımız saklıdır. / We reserve the right to change technical informations.

KOMPAKT MERKEZİ SİSTEM - COMPACT CENTRAL SYSTEM

ÜRÜN KOD / PRODUCT CODE	MODEL - MİKTAR / MODEL - QUANTITY	R448A-R449A KAPASİTE / CAPACITY (Kilowatt) EN12900 (Subcooling OK, Return Gas 20 °C)								
		-25°C			-30°C			-35°C		
		45	50	55	45	50	55	45	50	55
CMC-SL-02F-1,70S-T56B	B1.5-10.1Y - (2)	3,6	3,14	2,66	2,56	2,18	1,78	1,7	1,38	N/A
CMC-SL-02F-3,02S-T56B	D2-13.1Y - (2)	5,9	5,26	4,62	4,32	3,8	3,3	3,02	2,6	N/A
CMC-SL-02F-3,52S-T56B	D2-15.1Y - (2)	6,9	6,16	5,42	5,06	4,46	3,88	3,52	3,02	N/A
CMC-SL-02F-4,78S-T56B	D4-19.1Y - (2)	8,96	8,08	7,22	6,7	6	5,3	4,78	4,22	N/A
CMC-SL-02F-5,88S-T56B	Q4-25.1Y - (2)	11,22	10,06	8,9	8,32	7,4	6,48	5,88	5,14	N/A
CMC-SL-02F-6,12S-T56B	Q5-28.1Y - (2)	12,46	11,26	9,98	9,1	8,04	6,86	6,12	5,08	N/A
CMC-SL-02F-7,12S-T56B	Q5-33.1Y - (2)	14,54	13,12	11,64	10,62	9,36	8	7,12	5,92	N/A
CMC-SL-03F-6,15S-T56B	D3-16.1Y - (3)	11,55	10,41	9,27	8,58	7,68	6,75	6,15	5,4	N/A
CMC-SL-03F-7,83S-T56B	Q4-21.1Y - (3)	14,13	12,78	11,31	10,32	9,12	7,8	6,93	5,76	N/A
CMC-SL-03F-8,82S-T56B	Q4-25.1Y - (3)	16,83	15,09	13,35	12,48	11,1	9,72	8,82	7,71	N/A
CMC-SL-03F-8,94S-T56B	Q4-25.1Y - (2) + Q5-28.1Y - (1)	17,45	15,69	13,89	12,87	11,42	9,91	8,94	7,68	N/A
CMC-SL-03F-9,18S-T56B	Q5-28.1Y - (3)	18,69	16,89	14,97	13,65	12,06	10,29	9,18	7,62	N/A
CMC-SL-03F-9,68S-T56B	Q5-28.1Y - (2) + Q5-33.1Y - (1)	19,73	17,82	15,8	14,41	12,72	10,86	9,68	8,04	N/A
CMC-SL-03F-10,7S-T56B	Q5-33.1Y - (3)	21,81	19,68	17,46	15,93	14,04	12	10,68	8,88	N/A
CMC-SL-03F-13,5S-T56B	Q7-36.1Y - (3)	25,35	22,92	20,49	18,9	16,98	15,06	13,5	11,94	N/A
CMC-SL-03F-14,1S-T56B	S8-42Y - (3)	27,3	24,33	21,39	20,07	17,67	15,27	14,1	12,12	N/A
CMC-SL-03F-14,5S-T56B	S8-42Y - (2) + S10-52Y - (1)	28,78	25,51	22,28	20,97	18,33	15,71	14,54	12,38	N/A
CMC-SL-03F-14,9S-T56B	S8-42Y - (1) + S10-52Y - (2)	30,26	26,69	23,17	21,87	18,99	16,15	14,98	12,64	N/A
CMC-SL-03F-15,4S-T56B	S10-52Y - (3)	31,74	27,87	24,06	22,77	19,65	16,59	15,42	12,9	N/A
CMC-SL-04F-19,2S-T56B	S8-42Y - (3) + S10-52Y - (1)	37,88	33,62	29,41	27,66	24,22	20,8	19,24	16,42	N/A
CMC-SL-04F-19,7S-T56B	S8-42Y - (2) + S10-52Y - (2)	39,36	34,8	30,3	28,56	24,88	21,24	19,68	16,68	N/A
CMC-SL-04F-20,1S-T56B	S8-42Y - (1) + S10-52Y - (3)	40,84	35,98	31,19	29,46	25,54	21,68	20,12	16,94	N/A
CMC-SL-04F-20,6S-T56B	S10-52Y - (4)	42,32	37,16	32,08	30,36	26,2	22,12	20,56	17,2	N/A
CMC-SL-04F-22,9S-T56B	S10-52Y - (2) + S15-56Y - (2)	45,88	40,5	35,18	33,22	28,88	24,62	22,86	19,36	N/A
CMC-SL-04F-25,2S-T56B	S15-56Y - (4)	49,44	43,84	38,28	36,08	31,56	27,12	25,16	21,52	N/A
CMC-SL-04F-29,1S-T56B	V15-59Y - (4)	55,68	49,88	43,96	41,24	36,48	31,52	29,04	25,08	N/A
CMC-SL-04F-31,0S-T56B	V15-59Y - (3) + V15-71Y - (1)	58,93	52,92	46,85	43,79	38,88	33,84	31,02	26,96	N/A
CMC-SL-04F-33,0S-T56B	V15-59Y - (2) + V15-71Y - (2)	62,18	55,96	49,74	46,34	41,28	36,16	33	28,84	N/A
CMC-SL-04F-35,0S-T56B	V15-59Y - (1) + V15-71Y - (3)	65,43	59	52,63	48,89	43,68	38,48	34,98	30,72	N/A
CMC-SL-04F-37,0S-T56B	V15-71Y - (4)	68,68	62,04	55,52	51,44	46,08	40,8	36,96	32,6	N/A
CMC-SL-04F-42,0S-T56B	V15-71Y - (2) + V20-84Y - (2)	76,36	69,28	62,32	57,78	52,12	46,6	42,04	37,54	N/A
CMC-SL-04F-47,1S-T56B	V20-84Y - (4)	84,04	76,52	69,12	64,12	58,16	52,4	47,12	42,48	N/A

KOMPAKT MERKEZİ SİSTEM - COMPACT CENTRAL SYSTEM

ÜRÜN KOD / PRODUCT CODE	MODEL - MİKTAR / QUANTITY	KAPASİTE / CAPACITY	GÜÇ / POWER KW	GRUP ÖLÇÜLERİ / DIMENSIONS EN X BOY X YÜKS. / WIDTH X LENGTH X HEIGHT MM	BAĞLANTILAR / CONNECTIONS			FAN / FAN 900 RPM			ELEKTRİK / ELECTRICAL	
					EMİŞ / SUCTION	LİKİT / LIQUID	ADET / QTY.	ÇAP / DIA. MM	ADET / QTY.	GÜÇ / POWER KW	VOLTAJ / VOLTAGE	MAK. GÜÇ MAX. POWER KW
CMC-CL-02C-2,72S-T56B	ZF 08 K4E - (2)	2,72	3,24	850 x 1550 x 1900	28	12	1	450	2	0,33	T5	3,57
CMC-CL-02C-3,16S-T56B	ZF 09 K4E - (2)	3,16	3,26	850 x 1550 x 1900	28	12	1	450	2	0,33	T5	3,59
CMC-CL-02C-3,92S-T56B	ZF 11 K4E - (2)	3,92	4,44	850 x 1550 x 1900	28	12	1	450	2	0,33	T5	4,77
CMC-CL-02C-4,58S-T56B	ZF 13 K4E - (2)	4,58	4,7	850 x 1550 x 1900	35	16	1	450	2	0,33	T5	5,03
CMC-CL-02C-5,64S-T56B	ZF 15 K4E - (2)	5,64	6,28	850 x 1550 x 1900	35	16	1	450	2	0,33	T5	6,61
CMC-CL-02C-6,76S-T56B	ZF 18 K4E - (2)	6,76	8,58	850 x 1550 x 1900	42	18	1	500	2	0,48	T5	9,06
CMC-CL-02C-5,88S-T56B	ZF 11 K4E - (3)	5,88	6,66	850 x 2150 x 1900	35	16	1	500	3	0,72	T5	7,38
CMC-CL-03C-6,87S-T56B	ZF 13 K4E - (3)	6,87	7,05	850 x 2150 x 1900	42	18	1	500	3	0,72	T5	7,77
CMC-CL-03C-8,46S-T56B	ZF 15 K4E - (3)	8,46	9,42	850 x 2150 x 1900	42	18	1	500	3	0,72	T5	10,14
CMC-CL-03C-10,1S-T56B	ZF 18 K4E - (3)	10,1	12,87	850 x 2150 x 1900	54	22	1	500	3	0,72	T5	13,59
CMC-CL-03C-13,1S-T56B	ZF 25 K5E - (3)	13,1	12,69	850 x 2150 x 1900	54	22	1	500	3	0,72	T5	13,41
CMC-CL-03C-17,1S-T56B	ZF 34 K5E - (3)	17,1	17,28	1000 x 2450 x 1900	66	28	1	630	3	2,1	T5	19,38
CMC-CL-03C-18,4S-T56B	ZF 34 K5E - (2) + ZF 41 K5E - (1)	18,4	17,97	1000 x 2450 x 1900	66	28	1	630	3	2,1	T5	20,07
CMC-CL-03C-19,7S-T56B	ZF 34 K5E - (1) + ZF 41 K5E - (2)	19,7	18,66	1000 x 2450 x 1900	66	28	1	630	3	2,1	T5	20,76
CMC-CL-03C-21,0S-T56B	ZF 41 K5E - (3)	21	19,35	1000 x 2450 x 1900	66	28	1	630	3	2,1	T5	21,45
CMC-CL-03C-22,6S-T56B	ZF 41 K5E - (2) + ZF 49 K5E - (1)	22,6	21,55	1000 x 2450 x 1900	66	28	1	630	3	2,1	T5	23,65
CMC-CL-03C-24,1S-T56B	ZF 41 K5E - (1) + ZF 49 K5E - (2)	24,1	23,75	1000 x 2800 x 2300	66	28	1	630	3	2,1	T5	25,85
CMC-CL-03C-25,7S-T56B	ZF 49 K5E - (3)	25,7	25,95	1000 x 2800 x 2300	54	22	2	630	3	2,1	T5	28,05
CMC-CL-03C-26,6S-T56B	ZF 49 K5E - (2) + ZF 54 K5E - (1)	26,6	26,07	1000 x 2800 x 2300	54	22	2	630	3	2,1	T5	28,17
CMC-CL-03C-27,5S-T56B	ZF 49 K5E - (1) + ZF 54 K5E - (2)	27,5	26,19	1000 x 2800 x 2300	54	22	2	630	3	2,1	T5	28,29
CMC-CL-03C-28,4S-T56B	ZF 54 K5E - (3)	28,4	26,31	1000 x 2800 x 2300	66	28	2	630	3	2,1	T5	28,41
CMC-CL-04C-11,3S-T56B	ZF 15 K4E - (4)	11,3	12,56	850 x 2150 x 1900	54	22	1	500	3	0,72	T5	13,28
CMC-CL-04C-13,5S-T56B	ZF 18 K4E - (4)	13,5	17,16	850 x 2150 x 1900	54	22	1	500	3	0,72	T5	17,88
CMC-CL-04C-17,4S-T56B	ZF 25 K5E - (4)	17,4	16,92	1000 x 2450 x 1900	66	28	1	630	3	2,1	T5	19,02
CMC-CL-04C-22,8S-T56B	ZF 34 K5E - (4)	22,8	23,04	1000 x 2800 x 2300	66	28	1	630	3	2,1	T5	25,14
CMC-CL-04C-28,0S-T56B	ZF 41 K5E - (4)	28	25,8	1000 x 2800 x 2300	54	22	2	630	3	2,1	T5	27,9
CMC-CL-04C-34,2S-T56B	ZF 49 K5E - (4)	34,2	34,6	1100 x 2800 x 2500	66	28	2	800	2	3,88	T5	38,48
CMC-CL-04C-37,9S-T56B	ZF 54 K5E - (4)	37,9	35,08	1100 x 3400 x 2500	80	35	2	800	3	5,82	T5	40,9
CMC-CL-05C-14,1S-T56B	ZF 15 K4E - (5)	14,1	15,7	850 x 2800 x 2300	54	22	1	500	4	0,96	T5	16,66
CMC-CL-05C-16,9S-T56B	ZF 18 K4E - (5)	16,9	21,45	850 x 2800 x 2300	66	28	1	500	4	0,96	T5	22,41
CMC-CL-05C-21,8S-T56B	ZF 25 K5E - (5)	21,8	21,15	850 x 2800 x 2300	66	28	1	500	4	0,96	T5	22,11
CMC-CL-05C-28,6S-T56B	ZF 34 K5E - (5)	28,6	28,8	1100 x 2800 x 2500	54	22	2	800	2	3,88	T5	32,68
CMC-CL-05C-35,0S-T56B	ZF 41 K5E - (5)	35	32,25	1100 x 2800 x 2500	66	28	2	800	2	3,88	T5	36,13
CMC-CL-05C-42,8S-T56B	ZF 49 K5E - (5)	42,8	43,25	1100 x 3400 x 2500	80	35	2	800	3	5,82	T5	49,07
CMC-CL-05C-47,4S-T56B	ZF 54 K5E - (5)	47,4	43,85	1100 x 4400 x 2500	80	35	2	800	4	7,76	T5	51,61

Capacity Values Specified In The Code : Evap. Temp. : -35 °C Condensing Temp. 45 °C . According To EN12900 Subcooling OK, Return Gas 20 °C

- Teknik bilgileri değiştirme hakkımız saklıdır. / We reserve the right to change technical informations.

KOMPAKT MERKEZİ SİSTEM - COMPACT CENTRAL SYSTEM

ÜRÜN KOD / PRODUCT CODE	MODEL - MİKTAR / MODEL - QUANTITY	R448A-R449A KAPASİTE / CAPACITY (Kilowatt) EN12900 (Subcooling OK, Return Gas 20 °C)								
		-25°C			-30°C			-35°C		
		45	50	55	45	50	55	45	50	55
CMC-CL-02C-2,72S-T56B	ZF 08 K4E - (2)	4,32	4,06	3,8	3,44	3,24	3,04	2,72	2,56	2,4
CMC-CL-02C-3,16S-T56B	ZF 09 K4E - (2)	5	4,72	4,42	4	3,78	3,54	3,16	3	2,8
CMC-CL-02C-3,92S-T56B	ZF 11 K4E - (2)	6,2	5,84	5,46	4,98	4,68	4,36	3,92	3,68	3,4
CMC-CL-02C-4,58S-T56B	ZF 13 K4E - (2)	7,28	6,82	6,32	5,82	5,44	5,04	4,58	4,28	3,96
CMC-CL-02C-5,64S-T56B	ZF 15 K4E - (2)	8,9	8,26	7,58	7,12	6,62	6,08	5,64	5,24	4,82
CMC-CL-02C-6,76S-T56B	ZF 18 K4E - (2)	10,98	10,2	9,36	8,72	8,06	7,32	6,76	6,16	5,48
CMC-CL-02C-5,88S-T56B	ZF 11 K4E - (3)	9,3	8,76	8,19	7,47	7,02	6,54	5,88	5,52	5,1
CMC-CL-03C-6,87S-T56B	ZF 13 K4E - (3)	10,92	10,23	9,48	8,73	8,16	7,56	6,87	6,42	5,94
CMC-CL-03C-8,46S-T56B	ZF 15 K4E - (3)	13,35	12,39	11,37	10,68	9,93	9,12	8,46	7,86	7,23
CMC-CL-03C-10,1S-T56B	ZF 18 K4E - (3)	16,47	15,3	14,04	13,08	12,09	10,98	10,14	9,24	8,22
CMC-CL-03C-13,1S-T56B	ZF 25 K5E - (3)	20,79	19,44	18,03	16,59	15,54	14,4	13,08	12,21	11,34
CMC-CL-03C-17,1S-T56B	ZF 34 K5E - (3)	27,6	25,8	23,91	21,96	20,52	19,02	17,13	15,99	14,82
CMC-CL-03C-18,4S-T56B	ZF 34 K5E - (2) + ZF 41 K5E - (1)	29,5	27,6	25,61	23,52	22,01	20,43	18,42	17,24	16
CMC-CL-03C-19,7S-T56B	ZF 34 K5E - (1) + ZF 41 K5E - (2)	31,4	29,4	27,31	25,08	23,5	21,84	19,71	18,49	17,18
CMC-CL-03C-21,0S-T56B	ZF 41 K5E - (3)	33,3	31,2	29,01	26,64	24,99	23,25	21	19,74	18,36
CMC-CL-03C-22,6S-T56B	ZF 41 K5E - (2) + ZF 49 K5E - (1)	35,9	33,6	31,14	28,66	26,81	24,91	22,56	21,14	19,62
CMC-CL-03C-24,1S-T56B	ZF 41 K5E - (1) + ZF 49 K5E - (2)	38,5	36	33,27	30,68	28,63	26,57	24,12	22,54	20,88
CMC-CL-03C-25,7S-T56B	ZF 49 K5E - (3)	41,1	38,4	35,4	32,7	30,45	28,23	25,68	23,94	22,14
CMC-CL-03C-26,6S-T56B	ZF 49 K5E - (2) + ZF 54 K5E - (1)	42,4	39,75	36,85	33,8	31,6	29,42	26,6	24,91	23,17
CMC-CL-03C-27,5S-T56B	ZF 49 K5E - (1) + ZF 54 K5E - (2)	43,7	41,1	38,3	34,9	32,75	30,61	27,52	25,88	24,2
CMC-CL-03C-28,4S-T56B	ZF 54 K5E - (3)	45	42,45	39,75	36	33,9	31,8	28,44	26,85	25,23
CMC-CL-04C-11,3S-T56B	ZF 15 K4E - (4)	17,8	16,52	15,16	14,24	13,24	12,16	11,28	10,48	9,64
CMC-CL-04C-13,5S-T56B	ZF 18 K4E - (4)	21,96	20,4	18,72	17,44	16,12	14,64	13,52	12,32	10,96
CMC-CL-04C-17,4S-T56B	ZF 25 K5E - (4)	27,72	25,92	24,04	22,12	20,72	19,2	17,44	16,28	15,12
CMC-CL-04C-22,8S-T56B	ZF 34 K5E - (4)	36,8	34,4	31,88	29,28	27,36	25,36	22,84	21,32	19,76
CMC-CL-04C-28,0S-T56B	ZF 41 K5E - (4)	44,4	41,6	38,68	35,52	33,32	31	28	26,32	24,48
CMC-CL-04C-34,2S-T56B	ZF 49 K5E - (4)	54,8	51,2	47,2	43,6	40,6	37,64	34,24	31,92	29,52
CMC-CL-04C-37,9S-T56B	ZF 54 K5E - (4)	60	56,6	53	48	45,2	42,4	37,92	35,8	33,64
CMC-CL-05C-14,1S-T56B	ZF 15 K4E - (5)	22,25	20,65	18,95	17,8	16,55	15,2	14,1	13,1	12,05
CMC-CL-05C-16,9S-T56B	ZF 18 K4E - (5)	27,45	25,5	23,4	21,8	20,15	18,3	16,9	15,4	13,7
CMC-CL-05C-21,8S-T56B	ZF 25 K5E - (5)	34,65	32,4	30,05	27,65	25,9	24	21,8	20,35	18,9
CMC-CL-05C-28,6S-T56B	ZF 34 K5E - (5)	46	43	39,85	36,6	34,2	31,7	28,55	26,65	24,7
CMC-CL-05C-35,0S-T56B	ZF 41 K5E - (5)	55,5	52	48,35	44,4	41,65	38,75	35	32,9	30,6
CMC-CL-05C-42,8S-T56B	ZF 49 K5E - (5)	68,5	64	59	54,5	50,75	47,05	42,8	39,9	36,9
CMC-CL-05C-47,4S-T56B	ZF 54 K5E - (5)	75	70,75	66,25	60	56,5	53	47,4	44,75	42,05

KOMPAKT MERKEZİ SİSTEM - COMPACT CENTRAL SYSTEM

ÜRÜN KOD / PRODUCT CODE	MODEL - MİKTAR / QUANTITY	KAPASİTE / CAPACITY	GÜÇ / POWER KW	GRUP ÖLÇÜLERİ / DIMENSIONS EN X BOY X YÜK. / WIDTH X LENGTH X HEIGHT MM	BAĞLANTILAR / CONNECTIONS			FAN / FAN 900 RPM			ELEKTRİK / ELEC- TRICAL	
					EMİŞ / SUCT. MM	LİKİT / LIQUID MM	ADET / QTY.	ÇAP / DIA. MM	ADET / QTY.	GÜÇ / POWER KW	VOLTAJ / VOLTAGE	MAK. GÜÇ / MAK. POWER KW
CMC-CL-02E-2,96S-T56B	SE2008GS-O - (2)	2,96	2,88	850 x 1550 x 1900	28	12	1	450	2	0,33	T5	3,21
CMC-CL-02E-3,34S-T56B	SE2010GS-O - (2)	3,34	3,5	850 x 1550 x 1900	28	12	1	450	2	0,33	T5	3,83
CMC-CL-02E-4,40S-T56B	SE2012GS-O - (2)	4,4	5,08	850 x 1550 x 1900	35	12	1	450	2	0,33	T5	5,41
CMC-CL-02E-5,20S-T56B	SE2014GS-O - (2)	5,2	4,82	850 x 1550 x 1900	35	16	1	450	2	0,33	T5	5,15
CMC-CL-02E-6,00S-T56B	SE2017GS-O - (2)	6	5,54	850 x 1550 x 1900	35	16	1	450	2	0,33	T5	5,87
CMC-CL-02E-6,98S-T56B	SE2020GS-O - (2)	6,98	6,44	850 x 1550 x 1900	42	16	1	500	2	0,48	T5	6,92
CMC-CL-02E-6,60S-T56B	SE2012GS-O - (3)	6,6	7,62	850 x 2150 x 1900	42	16	1	500	3	0,72	T5	8,34
CMC-CL-03E-7,80S-T56B	SE2014GS-O - (3)	7,8	7,23	850 x 2150 x 1900	42	16	1	500	3	0,72	T5	7,95
CMC-CL-03E-9,00S-T56B	SE2017GS-O - (3)	9	8,31	850 x 2150 x 1900	54	16	1	500	3	0,72	T5	9,03
CMC-CL-03E-10,5S-T56B	SE2020GS-O - (3)	10,47	9,66	850 x 2150 x 1900	54	16	1	500	3	0,72	T5	10,38
CMC-CL-04E-8,80S-T56B	SE2012GS-O - (4)	8,8	10,16	850 x 2150 x 1900	54	16	1	500	3	0,72	T5	10,88
CMC-CL-04E-10,4S-T56B	SE2014GS-O - (4)	10,4	9,64	850 x 2150 x 1900	54	16	1	500	3	0,72	T5	10,36
CMC-CL-04E-12,0S-T56B	SE2017GS-O - (4)	12	11,08	850 x 2150 x 1900	54	16	1	500	3	0,72	T5	11,8
CMC-CL-04E-14,0S-T56B	SE2020GS-O - (4)	13,96	12,88	850 x 2150 x 1900	66	18	1	500	3	0,72	T5	13,6
CMC-CL-05E-11,0S-T56B	SE2012GS-O - (5)	11	12,7	1000 x 2450 x 1900	54	16	1	630	3	2,1	T5	14,8
CMC-CL-05E-13,0S-T56B	SE2014GS-O - (5)	13	12,05	1000 x 2450 x 1900	66	18	1	630	3	2,1	T5	14,15
CMC-CL-05E-15,0S-T56B	SE2017GS-O - (5)	15	13,85	1000 x 2450 x 1900	66	22	1	630	3	2,1	T5	15,95
CMC-CL-05E-17,5S-T56B	SE2020GS-O - (5)	17,45	16,1	1000 x 2450 x 1900	66	22	1	630	3	2,1	T5	18,2

Capacity Values Specified In The Code : Evap. Temp. : -35 °C Condensing Temp. 45 °C . According To EN12900 Subcooling OK, Return Gas 20 °C

- Teknik bilgileri değiştirme hakkımız saklıdır. / We reserve the right to change technical informations.

KOMPAKT MERKEZİ SİSTEM - COMPACT CENTRAL SYSTEM

ÜRÜN KOD / PRODUCT CODE	MODEL - MİKTAR / MODEL - QUANTITY	R448A-R449A KAPASİTE / CAPACITY (Kilowatt) EN12900 (Subcooling OK, Return Gas 20 °C)								
		-25°C			-30°C			-35°C		
		45	50	55	45	50	55	45	50	55
CMC-CL-02E-2,96S-T56B	SE2008GS-O - (2)	4,42	4,16	3,88	3,62	3,42	3,2	2,96	2,82	2,68
CMC-CL-02E-3,34S-T56B	SE2010GS-O - (2)	5,1	4,76	4,42	4,14	3,88	3,6	3,34	3,16	2,94
CMC-CL-02E-4,40S-T56B	SE2012GS-O - (2)	6,68	6,3	5,9	5,44	5,14	4,82	4,4	4,18	3,94
CMC-CL-02E-5,20S-T56B	SE2014GS-O - (2)	7,92	7,3	6,66	6,44	5,94	5,44	5,2	4,8	4,44
CMC-CL-02E-6,00S-T56B	SE2017GS-O - (2)	9,26	8,44	7,64	7,48	6,84	6,22	6	5,5	5,02
CMC-CL-02E-6,98S-T56B	SE2020GS-O - (2)	10,7	10	9,26	8,66	8,12	7,54	6,98	6,58	6,12
CMC-CL-02E-6,60S-T56B	SE2012GS-O - (3)	10,02	9,45	8,85	8,16	7,71	7,23	6,6	6,27	5,91
CMC-CL-03E-7,80S-T56B	SE2014GS-O - (3)	11,88	10,95	9,99	9,66	8,91	8,16	7,8	7,2	6,66
CMC-CL-03E-9,00S-T56B	SE2017GS-O - (3)	13,89	12,66	11,46	11,22	10,26	9,33	9	8,25	7,53
CMC-CL-03E-10,5S-T56B	SE2020GS-O - (3)	16,05	15	13,89	12,99	12,18	11,31	10,47	9,87	9,18
CMC-CL-04E-8,80S-T56B	SE2012GS-O - (4)	13,36	12,6	11,8	10,88	10,28	9,64	8,8	8,36	7,88
CMC-CL-04E-10,4S-T56B	SE2014GS-O - (4)	15,84	14,6	13,32	12,88	11,88	10,88	10,4	9,6	8,88
CMC-CL-04E-12,0S-T56B	SE2017GS-O - (4)	18,52	16,88	15,28	14,96	13,68	12,44	12	11	10,04
CMC-CL-04E-14,0S-T56B	SE2020GS-O - (4)	21,4	20	18,52	17,32	16,24	15,08	13,96	13,16	12,24
CMC-CL-05E-11,0S-T56B	SE2012GS-O - (5)	16,7	15,75	14,75	13,6	12,85	12,05	11	10,45	9,85
CMC-CL-05E-13,0S-T56B	SE2014GS-O - (5)	19,8	18,25	16,65	16,1	14,85	13,6	13	12	11,1
CMC-CL-05E-15,0S-T56B	SE2017GS-O - (5)	23,15	21,1	19,1	18,7	17,1	15,55	15	13,75	12,55
CMC-CL-05E-17,5S-T56B	SE2020GS-O - (5)	26,75	25	23,15	21,65	20,3	18,85	17,45	16,45	15,3