



Çift Kademeli Merkezi Sistem

Two Stage Central System



MERKEZİ SİSTEM KABİNLİ & KABİNSİZ MODEL - CENTRAL SYSTEM WITH CABIN & WITHOUT CABIN MODEL

ÜRÜN KOD / PRODUCT CODE	MODEL - MİKTAR / QUANTITY	KAPASİTE / CAPACITY	GÜÇ / POWER KW	GRUP ÖLÇÜLERİ / DIMENSIONS EN X BOY X YÜKS. / WIDTH X LENGTH X HEIGHT MM	BAĞLANTILAR / CONNECTIONS			FAN / FAN 900 RPM			ELEKTRİK / ELEC- TRICAL	
					EMİŞ / SUCT. MM	LİKİT / LIQUID MM	ADET QTY	ÇAP / DIA. MM	ADET / QTY.	GÜÇ / POWER KW	VOLTAJ / VOLTAGE	MAK. GÜÇ MAK. POWER KW
CM*-TB-02B-7,36S-T56B	S4T-5.2Y - (2)	7,36	7,4	1150 x 2500 x 1350	54	18	1	500	3	0,72	T5	8,12
CM*-TB-02B-10,6S-T56B	S4N-8.2Y - (2)	10,6	10,52	1150 x 2500 x 1350	66	22	1	630	2	1,4	T5	11,92
CM*-TB-02B-15,8S-T56B	S4G-12.2Y - (2)	15,8	15,88	1150 x 2500 x 1350	54	18	2	630	2	1,4	T5	17,28
CM*-TB-03B-11,1S-T56B	S4T-5.2Y - (3)	11,1	11,1	1150 x 2500 x 1350	66	22	1	630	2	1,4	T5	12,5
CM*-TB-03B-15,7S-T56B	S4N-8.2Y - (3)	15,7	15,78	1150 x 2500 x 1350	54	18	2	630	2	1,4	T5	17,18
CM*-TB-03B-23,7S-T56B	S4G-12.2Y - (3)	23,7	23,82	1150 x 3400 x 1350	66	22	2	800	2	3,88	T5	27,7
CM*-TB-03B-35,6S-T56B	S6J-16.2Y - (3)	35,6	35,76	1150 x 3400 x 1350	80	28	2	800	3	5,82	T5	41,58
CM*-TB-03B-41,3S-T56B	S6H-20.2Y - (3)	41,3	41,46	1150 x 3400 x 1350	80	28	3	800	3	5,82	T5	47,28
CM*-TB-03B-47,4S-T56B	S6G-25.2Y - (3)	47,4	47,61	1150 x 3400 x 1350	80	28	3	800	4	7,76	T5	55,37
CM*-TB-03B-56,7S-T56B	S6F-30.2Y - (3)	56,7	56,94	1150 x 3400 x 1350	80	28	3	800	4	7,76	T5	64,7

CM*- : CMO- WITH CABIN - CMI- WITHOUT CABIN

Capacity Values Specified In The Code : Evap. Temp. : -40 °C Condensing Temp. 45 °C . According To EN12900 Subcooling OK, Return Gas 20 °C

- Teknik bilgileri değiştirme hakkımız saklıdır. / We reserve the right to change technical informations.

MERKEZİ SİSTEM KABİNLİ & KABİNSİZ MODEL - CENTRAL SYSTEM WITH CABIN & WITHOUT CABIN MODEL

ÜRÜN KOD / PRODUCT CODE	MODEL - MİKTAR / MODEL - QUANTITY	R448A-R449A KAPASİTE / CAPACITY (Kilowatt) EN12900 (Subcooling OK, Return Gas 20 °C)								
		-35°C			-40°C			-45°C		
		45	50	55	45	50	55	45	50	55
CM*-TB-02B-7,36S-T56B	S4T-5.2Y - (2)	9,38	9,12	8,94	7,36	7,1	6,9	5,62	5,38	5,18
CM*-TB-02B-10,6S-T56B	S4N-8.2Y - (2)	13,34	12,96	12,72	10,46	10,08	9,8	8	7,66	7,36
CM*-TB-02B-15,8S-T56B	S4G-12.2Y - (2)	20,14	19,56	19,2	15,82	15,24	14,8	12,08	11,56	11,12
CM*-TB-03B-11,1S-T56B	S4T-5.2Y - (3)	14,07	13,68	13,41	11,04	10,65	10,35	8,43	8,07	7,77
CM*-TB-03B-15,7S-T56B	S4N-8.2Y - (3)	20,01	19,44	19,08	15,69	15,12	14,7	12	11,49	11,04
CM*-TB-03B-23,7S-T56B	S4G-12.2Y - (3)	30,21	29,34	28,8	23,73	22,86	22,2	18,12	17,34	16,68
CM*-TB-03B-35,6S-T56B	S6J-16.2Y - (3)	45,36	44,07	43,26	35,61	34,32	33,33	27,21	26,04	25,05
CM*-TB-03B-41,3S-T56B	S6H-20.2Y - (3)	52,56	51,06	50,13	41,28	39,78	38,61	31,53	30,18	29,04
CM*-TB-03B-47,4S-T56B	S6G-25.2Y - (3)	60,3	58,62	57,54	47,37	45,66	44,34	36,21	34,65	33,36
CM*-TB-03B-56,7S-T56B	S6F-30.2Y - (3)	72,3	70,2	69	56,7	54,63	53,04	43,32	41,43	39,9
CM* - : CMO- WITH CABIN - CMI- WITHOUT CABIN										

MERKEZİ SİSTEM KABİNLİ & KABİNSİZ MODEL - CENTRAL SYSTEM WITH CABIN & WITHOUT CABIN MODEL

ÜRÜN KOD / PRODUCT CODE	MODEL - MİKTAR / QUANTITY	KAPASİTE / CAPACITY	GÜÇ / POWER KW	GRUP ÖLÇÜLERİ / DIMENSIONS EN X BOY X YÜKS. / WIDTH X LENGTH X HEIGHT MM	BAĞLANTILAR / CONNECTIONS			FAN / FAN 900 RPM			ELEKTRİK / ELECTRICAL	
					EMİŞ / SUCT. MM	LİQT / LIQUID MM	ADET / QTY.	ÇAP / DIA. MM	ADET / QTY.	GÜÇ / POWER KW	VOLTAJ / VOLTAGE	MAK. GÜÇ MAK. POWER / KW
CM*-TB-02D-20,4S-T56B	2S-H1500 - (2)	20,4	19,54	1150 x 2500 x 1350	66	22	2	630	3	2,1	T5	21,64
CM*-TB-02D-29,9S-T56B	2S-H2000 - (2)	29,9	28,28	1150 x 2500 x 1350	80	28	2	800	2	3,88	T5	32,16
CM*-TB-02D-32,1S-T56B	2S-H2500 - (2)	32,1	29,16	1150 x 2500 x 1350	80	28	2	800	2	3,88	T5	33,04
CM*-TB-03B-30,7S-T56B	2S-H1500 - (3)	30,7	29,31	1150 x 3400 x 1350	80	28	2	800	2	3,88	T5	33,19
CM*-TB-03B-44,9S-T56B	2S-H2000 - (3)	44,9	42,42	1150 x 3400 x 1350	80	28	3	800	3	5,82	T5	48,24
CM*-TB-03B-48,2S-T56B	2S-H2500 - (3)	48,2	43,74	1150 x 3400 x 1350	80	28	3	800	4	7,76	T5	51,5
CM*-TB-03B-56,4S-T56B	2S-H3000 - (3)	56,4	51,24	1150 x 3400 x 1350	80	28	3	800	4	7,76	T5	59
CM*-TB-03B-60,6S-T56B	2S-H3500 - (3)	60,6	54,81	1150 x 3400 x 1350	80	28	3	800	4	7,76	T5	62,57

CM* - : CMO- WITH CABIN - CMI- WITHOUT CABIN

Capacity Values Specified In The Code : Evap. Temp. : -40 °C Condensing Temp. 45 °C . According To EN12900 Subcooling OK, Return Gas 20 °C

- Teknik bilgileri değiştirme hakkımız saklıdır. / We reserve the right to change technical informations.

MERKEZİ SİSTEM KABİNLİ & KABİNSİZ MODEL - CENTRAL SYSTEM WITH CABIN & WITHOUT CABIN MODEL

ÜRÜN KOD / PRODUCT CODE	MODEL - MİKTAR / MODEL - QUANTITY	R448A-R449A KAPASİTE / CAPACITY (Kilowatt) EN12900 (Subcooling OK, Return Gas 20 °C)								
		-35°C			-40°C			-45°C		
		45	50	55	45	50	55	45	50	55
CM*-TB-02D-20,4S-T56B	2S-H1500 - (2)	26,12	25,4	24,68	20,44	19,88	19,34	15,76	15,32	14,88
CM*-TB-02D-29,9S-T56B	2S-H2000 - (2)	37,78	36,98	36,2	29,96	29,36	28,78	23,42	22,98	22,54
CM*-TB-02D-32,1S-T56B	2S-H2500 - (2)	40,68	39,72	38,78	32,14	31,4	30,68	25,02	24,46	23,92
CM*-TB-03B-30,7S-T56B	2S-H1500 - (3)	39,18	38,1	37,02	30,66	29,82	29,01	23,64	22,98	22,32
CM*-TB-03B-44,9S-T56B	2S-H2000 - (3)	56,67	55,47	54,3	44,94	44,04	43,17	35,13	34,47	33,81
CM*-TB-03B-48,2S-T56B	2S-H2500 - (3)	61,02	59,58	58,17	48,21	47,1	46,02	37,53	36,69	35,88
CM*-TB-03B-56,4S-T56B	2S-H3000 - (3)	71,49	69,69	67,95	56,4	55,05	53,73	43,86	42,84	41,82
CM*-TB-03B-60,6S-T56B	2S-H3500 - (3)	76,86	74,85	72,9	60,6	59,1	57,6	47,1	45,93	44,79
CM*- : CMO- WITH CABIN - CMI- WITHOUT CABIN										

MERKEZİ SİSTEM KABİNLİ & KABİNSİZ MODEL - CENTRAL SYSTEM WITH CABIN & WITHOUT CABIN MODEL

ÜRÜN KOD / PRODUCT CODE	MODEL - MİKTAR / QUANTITY	KAPASİTE / CAPACITY	GÜÇ / POWER KW	GRUP ÖLÇÜLERİ / DIMENSIONS EN X BOY X YÜKS. / WIDTH X LENGTH X HEIGHT MM	BAĞLANTILAR / CONNECTIONS			FAN / FAN 900 RPM			ELEKTRİK / ELECTRICAL	
					EMİŞ / SUCT. MM	LİKİT / LIQUID MM	ADET / QTY.	ÇAP / DIA. MM	ADET / QTY.	GÜÇ / POWER KW	VOLTAJ / VOLTAGE	MAK. GÜÇ MAK. POWER KW
CM*-TB-02F-7,52S-T56B	S5-26.16Y - (2)	7,52	7,06	1150 x 2500 x 1350	54	18	1	500	3	0,72	T5	7,78
CM*-TB-02F-8,10S-T56B	S7-27.19Y - (2)	8,1	7,84	1150 x 2500 x 1350	54	18	1	500	3	0,72	T5	8,56
CM*-TB-02F-11,1S-T56B	2V10-42.29Y - (2)	11,1	11,88	1150 x 2500 x 1350	66	22	1	630	2	1,4	T5	13,28
CM*-TB-03F-11,3S-T56B	S5-26.16Y - (3)	11,3	10,59	1150 x 2500 x 1350	66	22	1	630	2	1,4	T5	11,99
CM*-TB-03F-12,2S-T56B	S7-27.19Y - (3)	12,2	11,76	1150 x 2500 x 1350	66	22	1	630	2	1,4	T5	13,16
CM*-TB-03F-16,5S-T56B	2V10-42.29Y - (3)	16,5	17,82	1150 x 3400 x 1350	54	18	2	630	3	2,1	T5	19,92
CM*-TB-03F-22,7S-T56B	2Z15-60.30Y - (3)	22,7	25,62	1150 x 3400 x 1350	66	22	2	800	2	3,88	T5	29,5
CM*-TB-03F-27,5S-T56B	2Z20-72.36Y - (3)	27,5	30,72	1150 x 3400 x 1350	66	22	2	800	2	3,88	T5	34,6
CM*-TB-03F-32,6S-T56B	2Z25-84.42Y - (3)	32,6	35,82	1150 x 3400 x 1350	80	28	2	800	3	5,82	T5	41,64
CM*-TB-03F-40,4S-T56B	2Z30-102.51Y - (3)	40,4	44,7	1150 x 3400 x 1350	80	28	2	800	4	7,76	T5	52,46
CM*-TB-03F-44,1S-T56B	2Z35-112.56Y - (3)	44,1	48,66	1150 x 3400 x 1350	80	28	3	800	4	7,76	T5	56,42
CM*-TB-03F-48,4S-T56B	2Z40-123.62Y - (3)	48,4	53,49	1150 x 3400 x 1350	80	28	3	800	4	7,76	T5	61,25

CM* - : CMO- WITH CABIN - CMI- WITHOUT CABIN

Capacity Values Specified In The Code : Evap. Temp. : -40 °C Condensing Temp. 45 °C . According To EN12900 Subcooling OK, Return Gas 20 °C

- Teknik bilgileri değiştirme hakkımız saklıdır. / We reserve the right to change technical informations.

MERKEZİ SİSTEM KABİNLİ & KABİNSİZ MODEL - CENTRAL SYSTEM WITH CABIN & WITHOUT CABIN MODEL

ÜRÜN KOD / PRODUCT CODE	MODEL - MİKTAR / MODEL - QUANTITY	R448A-R449A KAPASİTE / CAPACITY (Kilowatt) EN12900 (Subcooling OK, Return Gas 20 °C)								
		-35°C			-40°C			-45°C		
		45	50	55	45	50	55	45	50	55
CM*-TB-02F-7,52S-T56B	S5-26.16Y - (2)	9,72	9,16	8,66	7,52	7,06	6,64	5,7	5,32	4,94
CM*-TB-02F-8,10S-T56B	S7-27.19Y - (2)	10,48	9,86	9,26	8,1	7,6	7,1	6,14	5,72	5,28
CM*-TB-02F-11,1S-T56B	2V10-42.29Y - (2)	14,32	13,54	12,76	11,02	10,4	9,76	8,38	7,86	7,28
CM*-TB-03F-11,3S-T56B	S5-26.16Y - (3)	14,58	13,74	12,99	11,28	10,59	9,96	8,55	7,98	7,41
CM*-TB-03F-12,2S-T56B	S7-27.19Y - (3)	15,72	14,79	13,89	12,15	11,4	10,65	9,21	8,58	7,92
CM*-TB-03F-16,5S-T56B	2V10-42.29Y - (3)	21,48	20,31	19,14	16,53	15,6	14,64	12,57	11,79	10,92
CM*-TB-03F-22,7S-T56B	2Z15-60.30Y - (3)	29,52	27,93	26,34	22,71	21,42	20,13	17,19	16,11	14,94
CM*-TB-03F-27,5S-T56B	2Z20-72.36Y - (3)	35,85	34,05	32,31	27,54	26,1	24,63	20,85	19,59	18,24
CM*-TB-03F-32,6S-T56B	2Z25-84.42Y - (3)	42,39	40,23	38,04	32,58	30,81	28,95	24,69	23,16	21,42
CM*-TB-03F-40,4S-T56B	2Z30-102.51Y - (3)	52,86	50,25	47,67	40,35	38,19	35,97	30,3	28,47	26,43
CM*-TB-03F-44,1S-T56B	2Z35-112.56Y - (3)	57,69	54,84	52,02	44,04	41,67	39,27	33,09	31,05	28,83
CM*-TB-03F-48,4S-T56B	2Z40-123.62Y - (3)	63,48	60,33	57,24	48,42	45,84	43,2	36,39	34,17	31,71
CM* - : CMO- WITH CABIN - CMI- WITHOUT CABIN										